



STONE LOOK

SLATE ATTACHÉ™

GLAZED PORCELAIN FLOOR & GLAZED CERAMIC MOSAIC
WITH STEPWISE™ TECHNOLOGY

SLATE ATTACHÉ™

GLAZED PORCELAIN FLOOR & GLAZED CERAMIC MOSAIC WITH STEPWISE™ TECHNOLOGY

Natural Patterns Defined by Rich Color Variations

Rugged and classic, Slate Attaché™ tile brings a combination of rustic durability and timeless warmth to any room. It is an impressive mix of both tone-on-tone and multicolor stone looks with all the benefits of durable porcelain. Rich but balanced color options help you distinguish your space. Available in two large sizes and coordinating 2 x 2 mosaics.

- CLASSIC SLATE LOOK

- Authentic stone-look tile offered in three modern tone-on-tone colors and a multi-color, high variation hue
- StepWise™ technology is available in Multi Brown and can be used outdoors.

- TRADITIONAL YET VERSATILE

- Beautiful slate look coordinates with 2 x 2 mosaics for a myriad of design schemes
- Durable porcelain offers expanded applications without the peeling or flaking associated with natural slate stone

STONE LOOK

USAGE



SPECIAL FEATURES

SEE CHARTS FOR FULL PRODUCT DETAILS

Cover photo features Slate Attaché™ Meta Light Gray 12 x 24 on the floor.
Above photo features Slate Attaché™ Meta White 12 x 24 on the floor.

SLATE ATTACHÉ™

GLAZED PORCELAIN FLOOR & GLAZED CERAMIC MOSAIC WITH STEPWISE™ TECHNOLOGY

SIZES:



24 x 24
Floor Tile



12 x 24
Floor Tile



2 x 2
Mosaic

FINISHES: MATTE

COLOR PALETTE



META
WHITE



META
LIGHT GRAY




META
DARK GRAY



MULTI
BROWN

FLOOR



META WHITE SA04



META LIGHT GRAY SA06



META DARK GRAY SA07



MULTI BROWN SA08*

GLAZED CERAMIC 2 x 2 MOSAIC



META WHITE SA04



META LIGHT GRAY SA06



META DARK GRAY SA07



MULTI BROWN SA08

* PORCELAIN FLOOR TILE FEATURING STEPWISE™ TECHNOLOGY

50% MORE
SLIP RESISTANT
THAN ORDINARY TILE*

*When compared to tile meeting ANSI standards.



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



INDOOR/OUTDOOR



SIMPLECLEAN™

VISIT THE WHY TILE PAGE AT WWW.DAL TILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

SLATE ATTACHÉ™

GLAZED PORCELAIN FLOOR & GLAZED CERAMIC MOSAIC WITH STEPWISE™ TECHNOLOGY

STONE LOOK



ALL STYLE. NO SLIPS.

Don't tip-toe through life. Step stylishly on non-slip tile that's 50% more slip resistant than ordinary tile. And because it's Daltile, you'll find beautiful natural looks that are waterproof, scratchproof, stainproof and dentproof.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 24 Floor Tile	(23-13/16" x 23-13/16") (60.48 cm x 60.48 cm)	5/16"	15.76	4
	12 x 24 Floor Tile	(11-7/8" x 23-5/8") (30.23 cm x 60.12 cm)	5/16"	17.60	9
	2 x 2 Mosaic (Dot-mounted)	(12" x 24" Sheet) (30.48 cm x 60.96 cm Sheet)	1/4"	24.00	12

▪ Not available with StepWise™ technology

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓**
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓*
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	✓**

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

* Multi Brown SA08 24 x 24 and 12 x 24 floor tile with StepWise™ technology only. For more information, visit daltile.com/StepWise.

** Mosaic only

Floor tile suitable for exterior applications (provided it is noted a suitable in applications chart above) in freezing and non-freezing climates when proper installation methods are followed.

Mosaic suitable for exterior wall applications (provided it is noted a suitable in applications chart above) in non-freezing climates only when proper installation methods are followed.

To learn more about Stepwise™ technology, visit daltile.com/Stepwise.

TRIM

	Type	Number	Size	Pieces/ Carton
	Bullnose	P43C9	3 x 12	30

Bullnose trim is intended to coordinate with floor tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern. When multiple sizes are installed in a modular pattern, please specify same size caliber at time of order)	 High (V3) (SA04, SA06, & SA07)  Random (V4) (SA08)
Mosaic: 1/8"	

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 3.0%
Breaking Strength	C648	> 275 lbs.	> 250 lbs.
Scratch Hardness	MOHS	8.0	8.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms	3	All Residential / Light Commercial
2 All Residential Areas	④	All Residential / Commercial

NOTES

Special consideration must be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit daltile.com.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at daltile.com/Factors.

 POST-CONSUMER RECYCLED MATERIALS

 PRE-CONSUMER RECYCLED MATERIALS

 REVEAL IMAGING®

 MADE IN THE U.S.A.

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.

ZEROTOX
Healthy Homes | Healthy Planet

CERTIFIED
PORCELAIN
TILE
0.05% or less water absorption



7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.

daltile
IMAGINE WHAT'S POSSIBLE™
©2022 Daltile (8/22)