



WOOD LOOK

SLEIGH CREEK™  
GLAZED PORCELAIN

 daltile®  
IMAGINE WHAT'S POSSIBLE™

# SLEIGH CREEK™

GLAZED PORCELAIN

## Wood Look Takes a New Shape

Sleigh Creek™ fills your space with the comfort and timeless look of hardwood. This realistic wood look is achieved by combining an authentic wood visual with six enriched wood tones on a hardwearing surface. Sleigh Creek offers a classic 6x36 plank tile as well as an 8" hexagon floor tile which adds a new stylish shape to wood look tile.

- FRESH TAKE ON A CLASSIC
  - Combines a timeless style and an enhanced color palette
  - 6x36 plank size with coordinating 8" hexagon floor tile
- WORRY FREE WOOD LOOK
  - High moisture resistance is perfect for kitchens and bathroom installations
  - Long lasting scratch-resistant and dentproof surface

WOOD  
LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER  
FLOOR



EXTERIOR  
FLOOR



STEPWISE™



TRU-EDGE™



MADE IN  
THE U.S.A.



LARGE  
FORMAT



MOSAIC/  
DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



LOW HIGH

NOT APPLICABLE  
FOR ALL PRODUCTS  
IN THIS SERIES. SEE  
CHARTS FOR FULL  
PRODUCT DETAILS.

SPECIAL FEATURES

Cover photo features Sleigh Creek™ Wagon 6 x 36 matte on the floor and Panoramic Porcelain Surfaces™ Couture Series Formation Gold on the wall.

Above photo features Sleigh Creek™ Stagecoach 6 x 36 matte on the floor, Panoramic Porcelain Surfaces™ Couture Series Silver Fusion on the side wall and Aesthetic™ Retrocube 12 x 36 on the back wall.

SIZES:



6 x 36  
Floor Tile



8" Hexagon  
Floor Tile

FINISHES: MATTE

COLOR PALETTE



CABRIOLET SK30



STAGECOACH SK31



CARRIAGE SK32



WAGON SK33



CHARIOT SK34



LANDAU SK35

FLOOR TILE




CABRIOLET SK30



STAGECOACH SK31



CARRIAGE SK32



WAGON SK33



CHARIOT SK34



LANDAU SK35

8" HEXAGON FLOOR TILE



CABRIOLET SK30



STAGECOACH SK31



CARRIAGE SK32



WAGON SK33



CHARIOT SK34



LANDAU SK35



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

# SLEIGH CREEK™

GLAZED PORCELAIN

WOOD LOOK

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	6 x 36 Floor Tile	(5-7/8" x 35-7/16") (15.00 cm x 90.00 cm)	5/16"	13.05	9
	8" Hexagon Floor Tile	(7-7/8" x 9-1/8") (20.04 cm x 23.16 cm)	5/16"	9.37	25

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltile.com/DCOF](http://daltile.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

## TRIM

Type	Number	Size	Pieces/ Carton
 Bullnose	P43H9	3 x 18	16

## INSTALLATION

Grout Joint Recommendation	Shade Variation
----------------------------	-----------------

3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)



## PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [daltile.com/information/TestResults](http://daltile.com/information/TestResults).

## DURABILITY

### Floor Surface Wear Resistance

1 Residential Bathrooms	3 All Residential / Light Commercial
2 All Residential Areas	④ All Residential / Commercial

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [daltile.com/Factors](http://daltile.com/Factors).

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [daltile.com/LargeTiles](http://daltile.com/LargeTiles) for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit [daltile.com](http://daltile.com).



All or select items within this series meet the requirements for these qualifications. For more information, visit [daltile.com](http://daltile.com).



7834 C.F. Hawn Freeway,  
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at [daltile.com](http://daltile.com).



©2021 Daltile (8/21)