



MONOCHROMATIC
LOOK

STENCIL™
GLAZED PORCELAIN

 daltile®
IMAGINE WHAT'S POSSIBLE™

STENCIL™

GLAZED PORCELAIN

Stencil™ delivers a pop of color and texture to your space. This 4 x 12 tile is available in flat and linear surfaces as well as a half moon structure, which features a raised concave surface with semicircles on each end, forming a circle when installed together. All three structures are suitable for wall applications; the flat structure can also be installed in floor applications. Stencil can deliver the neutral ambience of white, beige or grey, or can wow with the eye-catching colors of mint, indigo, blush or berry. Mix and match colors and textures to create fun, playful spaces.



Cover photo features Stencil™ Beige 4 x 12 linear matte on the back wall and White on the column and front wall, Natural Quartzite White N6ir polished on the countertop and Assemble™ Magistrate 30 x 30 paver tile on the floor.

Above photo features Stencil™ Indigo, Beige and Grey 4 x 12 linear wall tile on the near wall, Indigo 4 x 12 half moon wall tile on the far wall and Sleigh Creek™ Stagecoach 6 x 36 matte on the floor.



MONOCHROMATIC
LOOK

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER
FLOOR



EXTERIOR
FLOOR



STEPWISE™



TRU-EDGE™



MADE IN
THE U.S.A.



LARGE
FORMAT



MOSAIC/
DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



GLAZED
PORCELAIN



LOW



HIGH

SPECIAL FEATURES

NOT APPLICABLE
FOR ALL PRODUCTS
IN THIS SERIES. SEE
CHARTS FOR FULL
PRODUCT DETAILS.

SIZES:



COLOR PALETTE

FINISHES: MATTE



FLAT FLOOR TILE



LINEAR WALL TILE



HALF MOON WALL TILE



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



CLIMATEPRO™



SIMPLICLEAN™

STENCIL™

GLAZED CERAMIC

MONOCHROMATIC LOOK

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	4 x 12 Flat Floor Tile	(3-1/2" x 11-13/16") (9.00 cm x 30.00 cm)	5/16"	8.72	30
	4 x 12 Linear Wall Tile	(3-1/2" x 11-13/16") (9.00 cm x 30.00 cm)	5/16"	8.72	30
	4 x 12 Half Moon Wall Tile	(3-1/2" x 11-13/16") (9.00 cm x 30.00 cm)	7/16"	5.81	20

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓*
Wet & Level – Interior Floor	≥ 0.42	✓*
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓*
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

* Floor tile only.

TRIM

Type	Number	Size	Pieces/ Carton
 12" Jolly	S1/212J	1/2 x 12	12

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16"	 Low (V1)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	7.5
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Use of a latex modified thin-set is recommended for installation. For more information, visit daltile.com.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.



LEARN MORE

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltile® products and information,
visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

©2022 Daltile (8/22)