

DECORATIVE

-0-5

21

UPTOWN GLASS

.....



GLASS MOSAICS

Create a Statement with Eye Catching Prints and Striking Finishes

With contemporary urban inspiration, this chic collection reflects the most current design trends. Featuring a range of beautiful solid colors as well as metallic elements sprinkled into marble visuals, Uptown Glass[®] mosaics allow easy style expression for accent walls, backsplashes and floors. Also, with the addition of new technology, many of the patterns and finishes in this collection are made to withstand pool and spa chemicals, providing an excellent choice to make a splash with pool or hot tub designs.

- FASHION FORWARD
 - Exotic prints, geometric patterns and beautiful iridescent tones make a bold and unique statement in any space
- ECO FRIENDLY

Contains 98% recycled content

PERFECT FOR MANY SPACES

Excellent choice for accent walls and backsplashes Many styles are suitable for pool use allowing for an impressive decorative accent

000

\$

UPTOWN GLASS[™]

GLASS MOSAICS


| SIZES:

1 x 1 Metro Mosaics (Mesh-mounted)

1" Hexagon Mosaic (Mesh-mounted)

FINISHES: MATTE | GLOSSY

1 x 1 METRO MOSAICS







1" HEXAGON MOSAIC




POSH CHIFFON UP27



POSH SPRITZER UP24*


MATTE ALABASTER UP20*



POSH BUBBLY UP28



POSH RESORT UP25*



MATTE EBONY UP22*

CARRARA UP23*



METRO GRAY UP08





0.0.0





* Suitable for floor use.



MATTE FROST

MOKA UP21*













SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DALTILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

POSH SPARKLER UP26*





UPTOWN GLASS[™]

GLASS MOSAICS

D	E	C	0	R.	A٦	V	F

SIZES	5				
			Thickness	Sq. Ft./ Carton	Pieces/ Carton
		(12-1/4" x 12-1/4" Sheet) (31.00 cm x 31.00 cm Sheet)	4.4 mm	21.00	20
		(11-3/4" x 11-1/2" Sheet) (30.00 cm x 29.00 cm Sheet)	4.4 mm	16.92	18

APPLICATIONS

Target DCOF wet	Suitable
N/A	✓*
≥ 0.42	✓*
≥ 0.42	✓*
≥ 0.60	
≥ 0.65	
N/A	~
N/A	
N/A	* **
	DCOF wet N/A ≥ 0.42 ≥ 0.42 ≥ 0.60 ≥ 0.65 N/A

A DCOF value of \geq 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest[™], visit daltile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Uptown Glass 1 x 1 Metro series contains Molten Glass. Molten glass characteristics include irregular edges and some variation in size. These characteristics are inherent in standard production. These subtle size and shape variations impact the final grout joint appearance and enhance the natural visual of this series.

- * 1" Hexagon mosaic UP20, UP21, UP22, UP23, UP24, UP25 and UP26 only.
- ** UP27, UP28, UP29 not suitable for pool linings.

INSTALLATION



PERFORMANCE CHARACTERISTICS

ASTM#	Floor / 1" Hexagon Result (UP20-UP26)	Metro & Wall / Hexagon Result (UP07, UP08, UP09, UP17, UP18, UP19, UP27, UP28, UP29)
C373	< 0.5%	< 0.5%
C648	> 250 lbs	> 250 lbs
MOHS	8.0	4.0
C650	Resistant	Resistant
C1027	N/A	N/A
	C373 C648 MOHS C650	ASTM# Result (UP20-UP26) C373 < 0.5%

For additional information on test results, visit us at: daltile.com/information/TestResults.

NOTES

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.2 standards.

Use of a white latex modified thin-set is recommended for installation.



All or select items within this series meet the requirements for these qualifications. For more product information, visit daltile.com.



7834 C.F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile[®] products and information, visit our website at **daltile.com**.

