



WOOD LOOK

WILLOW BEND™
GLAZED PORCELAIN

 daltile®
IMAGINE WHAT'S POSSIBLE™

WILLOW BEND™

GLAZED PORCELAIN

Delightful Style With Dramatic Size

Make your space more inviting with the delightful design of Willow Bend. Using Reveal Imaging® to create crisp and stunning graphics, this wood look porcelain tile inspires serenity. Offered in a 6 x 24 plank and featuring an even larger 6 x 36 size, Willow Bend embraces both traditional and modern styles.

- **IN-DEMAND COLORS AND SIZES**

- Two versatile plank sizes: 6 x 24 and an even larger 6 x 36 plank
- Popular wood colors including smoky brown and dark brown
- Reveal Imaging® technology creates crisp and stunning graphics

- **DURABLE DESIGN**

- Ease of maintenance and durability perfect for high-traffic areas
- Designed for both residential and commercial settings



Above and cover photos feature Willow Bend™ Dark Brown 6 x 24 on the floor.

WOOD
LOOK

USAGE



SEE CHARTS FOR FULL
PRODUCT DETAILS

SPECIAL FEATURES

SIZES:



6 x 36
Floor Tile



6 x 24
Floor Tile

FINISHES: MATTE

FLOOR TILE



DARK BROWN WB03



SMOKY BROWN WB02



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



CLIMATEPRO™





SIMPLICLEAN™

WILLOW BEND™

GLAZED PORCELAIN

WOOD LOOK

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	6 x 36 Floor Tile	(5-15/16" x 35-7/16") (15.19 cm x 90.00 cm)	5/16"	13.05	9
	6 x 24 Floor Tile	(6-1/16" x 23-7/8") (15.43 cm x 60.60 cm)	5/16"	16.10	16

APPLICATIONS


	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)	 High (V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: daltille.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1 Residential Bathrooms (3)	All Residential / Light Commercial
2 All Residential Areas	4 All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltille.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration must be given when installing tiles greater than 15 inches. Please refer to daltille.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit daltille.com.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltille.com.



7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltille® products and information, visit our website at daltille.com.



©2023 Daltille (7/23)