

STONE LOOK

XTERIORS™

ALL-WEATHER SOLUTIONS FOR EXTERIOR STYLE

BY  daltile

COURIER™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

TREAD™
PORCELAIN PAVERS

COURIER™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

Three warm shades modernize the ancient character of limestone in this outdoor TREAD™ pavers series, Courier. With a design distinguished by its natural and minimal patterning, and a versatile selection of sizes, this series brings contemporary taste in a 2cm paver. Courier's soft aesthetic pairs effortlessly with any style to offer a sleek, sophisticated touch.

STONE LOOK

USAGE



SPECIAL FEATURES



Cover and above photo feature Lookout, 24 x 24 2cm pavers on the patio floor.

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES:



24 x 48
Paver Tile



32 x 32
Paver Tile



24 x 48
Paver Tile



24 x 24
Paver Tile



14 x 15
Foglie Mosaic



12 x 11.5
Mosaic Blend

FINISHES: TEXTURED | MATTE

24 X 48 COLORBODY™ PORCELAIN PAVERS



LOOKOUT CR90



ROCKWELL CR91



RIVER CR92

24 X 24 COLORBODY™ PORCELAIN PAVERS



LOOKOUT CR90



ROCKWELL CR91



RIVER CR92

14 X 15 FOGLIE MOSAIC



LOOKOUT CR90



ROCKWELL CR91



RIVER CR92

12 X 11.5 MOSAIC BLEND



MIXED RIVER CR93

50% MORE
SLIP RESISTANT
THAN ORDINARY TILE*

*When compared to tile meeting ANSI standards.



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT*
*Not Applicable to Mesh-Mounted Mosaics



INDOOR/OUTDOOR



SIMPLICLEAN™

VISIT THE WHY TILE PAGE AT WWW.DALTILE.COM FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

COURIER™

COLORBODY™ PORCELAIN WITH STEPWISE™ TECHNOLOGY

STONE LOOK

SIZES

			Thickness	Finish	Made in U.S.A.
	48 x 48 Paver Tile**	47-3/16" x 47-3/16" (120.00 cm x 120.00 cm)	13/16" (2cm)	T	
	32 x 32 Paver Tile**	31-1/4" x 31-1/4" (79.50 cm x 79.50 cm)	13/16" (2cm)	T	
	24 x 48 Paver Tile	23-5/8" x 47-1/4" (60.00 cm x 120.00 cm)	13/16" (2cm)	T	
	24 x 24 Paver Tile*	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	13/16" (2cm)	T	
	14 x 15 Fogle Mosaic Tile**	13-7/16" x 14-15/16" Sheet (34.20 cm x 38.00 cm Sheet)	3/8"	M	
	12 x 11.5 Mosaic Blend Tile**	12-1/125" x 11-13/16" Sheet (30.50 cm x 30.00 cm Sheet)	3/8"	M	

T Textured Finish **M** Matte Finish
 * Stepwise available in 24 x 24 only.
 ** Available as special order only.

TRIM†

	Type
	Step Nose Tile
	Coping Tile

† Trim items available in many sizes and colors. Consult with your sales representative and/or design team for specifics.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓
Shower Floors – Standard Center Drain	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	✓
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit daltille.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

* Paver tile only.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.) Mosaic: 1/8"	Medium (V2)

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 0.5%
Breaking Strength	C1505	> 2000 lbf	> 275 lbf
Scratch Hardness	C1895	8.0	8.0
Chemical Resistance	C650	Resistant	Resistant
Abrasion Resistance	C1027	N/A	N/A

For additional information on test results, visit us at: daltille.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance		
1 Residential Bathrooms	3	All Residential / Light Commercial
2 All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.3 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltille.com/Factors,

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltille.com/LargeTiles.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.



All or select items within this series meet the requirements for these qualifications. For more information, visit daltille.com.



7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltille® products and information, visit our website at daltille.com.



IMAGINE WHAT'S POSSIBLE™

©2026 Daltille (02/26)