

ARTISTIC REFLECTIONS™

GLAZED CERAMIC WALL AND MOSAICS

MARAZZI®
DARE TO BE BOLD™

WALL



ARTISTIC REFLECTIONS™

Artistic Reflections™ combines a translucent glaze with an undulated surface, creating a handcrafted structure. A color palette of neutrals and trend-setting jewel tones add dimension and visual interest. Whether the preferred style is classic, edgy, modern, or mixed and matched to create an eclectic feel, Artistic Reflections seamlessly fits within a multitude of design trends.



Cover photo features Artic and Mist, 2 x 20 on the wall and Rain, 3" Hexagon Mosaic on the floor.
Above photo features Matte Artic and Wave, 2 x 20 on the wall.

FINISHES: MATTE | GLOSSY



WALL

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

2 X 20 WALL TILE



AE04 Artic / **AE05** Matte Artic



AE06 Mist / **AE07** Matte Mist



AE08 Rain / **AE09** Matte Rain



AE10 Onyx / **AE11** Matte Onyx



AE12 Wave



AE13 Rose



AE14 Haze



AE15 Twilight

2 X 10 WALL TILE



AE04 Artic / **AE05** Matte Artic



AE06 Mist / **AE07** Matte Mist



AE08 Rain / **AE09** Matte Rain



AE10 Onyx / **AE11** Matte Onyx



AE12 Wave



AE13 Rose



AE14 Haze



AE15 Twilight


3" HEXAGON MOSAIC TILE | 14 x 12 SHEET




AE04 Artic
AE05 Matte Artic



AE06 Mist
AE07 Matte Mist




AE08 Rain
AE09 Matte Rain




AE10 Onyx
AE11 Matte Onyx




AE12 Wave



AE13 Rose



AE14 Haze



AE15 Twilight



SLIP RESISTANT



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



SIMPLYCLEAN™

VISIT MARAZZITILE.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE | GLOSSY

USAGE

FLOORWALLCOUNTERTOPSHOWER FLOOR*EXTERIOR FLOOR*

MATERIAL

PRICING










SPECIAL FEATURES

LOWHIGH

STEPWISE™TRUEDGE™REVEAL SYNC'D™MADE IN THE U.S.A.LARGE FORMATMOSAIC/DECOENCAUSTICTERRAZZOFAVERCUSTOMIZE

WALL

SIZES

			Thickness	Finish
	2 x 20 Wall Tile	1-7/8" x 19-9/16" (4.90 cm x 49.80 cm)	3/8"	 
	2 x 10 Wall Tile	1-7/8" x 9-13/16" (4.90 cm x 24.87 cm)	5/16"	 
	3" Hexagon Mosaic Tile (Mesh-mounted)	11-13/16" x 14-3/16" Sheet (30.10 cm x 36.10 cm Sheet)	5/16"	 








 Glossy Finish  Matte Finish (Available in AE05, AE07, AE09, & AE11 only)

TRIM

Description	Number	Size	Shape	Finish
Jolly	S1/210J	1/2 x 10		 

 Glossy Finish  Matte Finish

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	 *
Wet & Level – Interior Floor	≥ 0.42	 *
Shower Floors – Standard Center Drain	≥ 0.42	 *
Shower Floors – Linear Drain	≥ 0.42 (Mosaic)	 *
	≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	 *
Pool Linings	N/A	 **

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazziusa.com/DCOF.


APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

* Matte mosaic tile only.

** Mosaic tile only.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Wall Tile: 1/16" Mosaic Tile: 1/8"	 Low Variation



PERFORMANCE CHARACTERISTICS

	ASTM#	Wall Result	Mosaic Result (Matte)	Mosaic Result (Glossy)
Water Absorption	C373	< 20%	< 20%	< 20%
Breaking Strength	C648	120-130 lbf	> 275 lbf	> 275 lbf
Scratch Hardness	C1895	4.0 - 6.0	8.0	4.0 - 6.0
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: marazziusa.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms		All Residential / Light Commercial*
	All Residential Areas*	4	All Residential / Commercial

* Matte mosaic tile only.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.


Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.


For additional information refer to "Factors to Consider" at: marazziusa.com/Factors.


Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazziusa.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

FEATURES

 PRE-CONSUMER RECYCLED MATERIALS

 REVEAL IMAGING®

 ZEROTOX

All or select items within this series meet the requirements for these qualifications. For more information visit marazziusa.com.