

# BASALTO™

COLORBODY™ PORCELAIN

TRUEEDGE™ | REVEAL IMAGING®

**MARAZZI**®

DARE TO BE BOLD™

## FLOOR TILE



**BT25** Pomice



**BT26** Sabbia



**BT27** Piombo



**BT28** Lava

## USAGE

Floors	Walls	Countertops
F	W	C

**SIZES**

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 48 Floor Tile	(23-7/16" x 46-15/16") (59.50 cm x 119.30 cm)	3/8"	15.52	2
	12 x 24 Floor Tile	(11-11/16" x 23-7/16") (29.65 cm x 59.50 cm)	3/8"	11.64	6
	32 x 32 Paver Tile*	(30-5/16" x 30-5/16") (79.50 cm x 79.50 cm)	13/16" 2cm	6.89	1
	20 x 40 Paver Tile*	(19-1/2" x 39-3/16") (49.50 cm x 99.50 cm)	13/16" 2cm	5.38	1

\* Special order

Special order colors only available in BT26, BT27 and BT28

**APPLICATIONS**

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	■
Wet & Level - Interior Floor	≥ 0.42	■
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	■ (2cm Paver Tile only)
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, marazzitile.com/DCOF.

**APPLICATION NOTES:**

Suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.

-  Floor Tile
-  Wall Tile
-  TruEdge™
-  Reveal Imaging®
-  Pre-Consumer Recycled Content



All or select items within this series meet the requirements for these qualifications. For more information visit marazzitile.com.

**TRIM**

Description	Number	Size	Shape
Floor Bullnose	S-43F9	3 x 24	
Floor Bullnose*	S-43U9	3 x 35	
Cove Base	S-36C9T	6 x 12	
Cove Base Outcorner	SC-36C9T	1 x 6	

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

\* Special order

**INSTALLATION**

Grout Joint Recommendation	Shade Variation
1/8" (3/16" when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%)	 Medium Variation

**PERFORMANCE CHARACTERISTICS**

	ASTM#	Floor Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs > 1000 lbs. (2cm)
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

**NOTES**

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazzitile.com/LargeTiles for more information.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.