

CLASSENTINO MARBLE™  
COLORBODY™ PORCELAIN

MARAZZI®  
DARE TO BE BOLD™

MARBLE LOOK



# CLASSENTINO MARBLE™

Elegant yet trending, Classentino Marble™ offers the bold, realistic look of marble in a porcelain tile. Available in both matte and polished looks in the popular 24x48, 24x24, and 12x24 floor tile sizes. Or, expand your horizons with the 2x3 Linear Hex mosaic, available in matte only



DARE TO BE BOLD



WITH MARAZZI DESIGNS

FINISHES: MATTE | POLISHED

<b>USAGE</b>			<b>MATERIAL</b>		<b>PRICING</b>		<b>SPECIAL FEATURES</b>								
FLOOR	WALL	COUNTERTOP	SHOWER FLOOR	EXTERIOR FLOOR	PC	LOW HIGH	STEPWISE™	TRUEEDGE™	MADE IN THE U.S.A.	LARGE FORMAT	MOSAIC/ DECO	ENCAUSTIC	TERRAZZO	PAVER	CUSTOMIZE

MARBLE LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

**COLORBODY™ PORCELAIN FLOOR TILE - AVAILABLE IN MATTE AND POLISHED**



**CT30** Palazzo White



**CT32** Coliseum Gray



**CT34** Centurio Black


**2 x 3 LINEAR HEX MOSAIC - MATTE**  
**12 x 12 SHEET**



**CT30** Palazzo White



**CT32** Coliseum Gray



**CT34** Centurio Black

SLIP RESISTANT	WATERPROOF	STAIN PROOF	DENT PROOF	SCRATCH-RESISTANT	FIRE-RESISTANT	CLIMATEPRO™	SIMPLICLEAN™

VISIT [MARAZZITILE.COM/WHYTILE](http://MARAZZITILE.COM/WHYTILE) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE | POLISHED

<b>USAGE</b>	<b>MATERIAL</b>	<b>PRICING</b>	<b>SPECIAL FEATURES</b>

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

MARBLE LOOK

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 48 Floor Tile	23-7/16" x 47-1/16" (59.50 cm x 119.50 cm)	3/8"	15.50	2
	24 x 24 Floor Tile*	23-7/16" x 23-7/16" (59.50 cm x 59.50 cm)	3/8"	11.63	3
	12 x 24 Floor Tile	11-11/16" x 23-7/16" (29.65 x 59.50 cm)	3/8"	9.69	5
	2 x 3 Linear Hex Mosaic* (Mesh-Mounted)	12-1/8" x 12-3/16" Sheet (30.81 cm x 30.94 cm Sheet)	3/8"	10.50	10

\*Only available in Matte

## TRIM

Description	Number	Size	Shape
Floor Bullnose	S43F9	3 x 24	

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position. Cove base and cove corner trim are suitable for non-freezing climates only.

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	■
Wet & Level – Interior Floor	≥ 0.42	■**
Shower Floors (Residential or Light Commercial)	≥ 0.42	■*
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	■*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [marazziusa.com/DCOF](http://marazziusa.com/DCOF).

### APPLICATION NOTES:

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Wall tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

\* Linear Hex Mosaic only. \*\* Matte Floor and Linear Hex Mosaic only.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
<p>Floor Tile: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%).</p> <p>Mosaic: 1/8"</p>	

## PERFORMANCE CHARACTERISTICS

	ASTM#	Matte Floor/ Linear Hex Mosaic Result	Polished Floor
Water Absorption	C373	< 0.5%	< 0.5%
Breaking Strength	C648	> 275 lbs	> 275 lbs
Scratch Hardness	MOHS	8.0	6.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at: [marazziusa.com/information/TestResults](http://marazziusa.com/information/TestResults).

## DURABILITY

### Floor Surface Wear Resistance

1	Residential Bathrooms	③	All Residential / Light Commercial*
2	All Residential Areas	④	All Residential / Commercial**

\* Polished \*\* Matte

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [marazziusa.com/Factors](http://marazziusa.com/Factors).

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [marazzitile.com/LargeTiles](http://marazzitile.com/LargeTiles) for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

## FEATURES



All or select items within this series meet the requirements for these qualifications. For more information visit [marazziusa.com](http://marazziusa.com).