

COSTA CLARA™
GLAZED CERAMIC

MARAZZI
DARE TO BE BOLD™

WALL



COSTA CLARA™

Costa Clara™ captures the essence of artisanal hand-made tiles with a refined coastal feel. This luminous wall tile with translucent glaze and soft undulations combine for a rich design aesthetic. A lavish sea of colors range from light beige to bright blue to deep red. Ideal for accent walls, bathrooms, or any space looking for a touch of hand-crafted elegance.



Cover photo features Blue Wave, 3 x 12 on the wall.
Above photo features Cloud, 3 x 12 and Deep Sea, 3 x 12 on the walls.

FINISHES: GLOSSY

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



WALL

WALL TILE



CC80 Cloud



CC81 Beach Sand



CC82 Pelican



CC83 Pebble Shore



CC85 Ocean Drive



CC86 Caribbean Teal



CC87 Blue Wave



CC89 Deep Sea



STAINPROOF



DENTPROOF



FIRE-RESISTANT



SIMPLECLEAN

VISIT MARAZZIUSA.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: GLOSSY

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



WALL

SIZES

			Thickness	Finish
	3 x 12 Wall Tile	3" x 11-7/8" (7.50 cm x 30.00 cm)	5/16"	G

G Glossy Finish

TRIM

Shape	Description	Number	Size	Finish
	Jolly	S1/212J	1/2 x 12	G

4 pieces per card, 6 cards per carton.

G Glossy Finish

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42	
	≥ 0.60	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazziusa.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8"	V1 Low Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20%
Breaking Strength	C648	120 - 230 lbf
Scratch Hardness	C1895	4.0 - 6.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

For additional information refer to "Factors to Consider" at: marazziusa.com/Factors.

FEATURES

PRE-CONSUMER RECYCLED MATERIALS

ZEROTOX
Healthy Homes | Healthy Planet

All or select items within this series meet the requirements for these qualifications. For more information visit marazziusa.com.