

FORGEHAUS™
COLORBODY™ PORCELAIN FLOOR & MOSAIC AND GLAZED CERAMIC WALL

MARAZZI 
DARE TO BE BOLD™

STONE LOOK



FORGEHAUS™

Forge a path where versatility meets style, the contemporary stone-look Forgehaus™ is a showcase of modern design, boasting dynamic graphics and rich variation. Large format floor options command any space, while the 12 x 24 Ripple wall tile and Trapezoid mosaic create a geometric illusion for the curious creative.



COVER PHOTO: BEAM
ABOVE PHOTO: FERRA

STONE LOOK

FINISHES: MATTE

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



STONE LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

COLORBODY™ PORCELAIN FLOOR TILE



FH10 Beam



FH11 Terra



FH12 Chroma



FH13 Basalt



FH10 Beam



FH11 Terra



FH12 Chroma



FH13 Basalt



SLIP RESISTANT



WATERPROOF



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT



FIRE-RESISTANT



CLIMATEPRO™



SIMPLECLEAN™

VISIT MARAZZIUSA.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE

USAGE			MATERIAL		PRICING		SPECIAL FEATURES								
															
FLOOR	WALL	COUNTERTOP	PC	CG	LOW	HIGH	STEPWISE™	TRUEEDGE™	MADE IN THE U.S.A.	LARGE FORMAT	MOSAIC/ DECO	ENCAUSTIC	TERRAZZO	PAVER	CUSTOMIZE

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

STONE LOOK

GLAZED CERAMIC WALL TILE - RIPPLE



FH10 Beam



FH11 Terra



FH12 Chroma



FH13 Basalt

COLORBODY™ PORCELAIN 2 x 4 TRAPEZOID MOSAIC



FH10 Beam



FH11 Terra



FH12 Chroma



FH13 Basalt

1/2 x 12 JOLLY TRIM



FH10 Beam



FH11 Terra



FH12 Chroma



FH13 Basalt

							
SLIP RESISTANT	WATERPROOF	STAIN PROOF	DENT PROOF	SCRATCH-RESISTANT	FIRE-RESISTANT	CLIMATEPRO™	SIMPLECLEAN™

VISIT MARAZZIUSA.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



STONE LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 48 Floor Tile	23-3/8" x 46-15/16" (59.44 cm x 119.20 cm)	5/16"	15.26	2
	24 x 24 Floor Tile	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	5/16"	15.21	4
	12 x 24 Floor Tile	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	5/16"	17.02	9
	12 x 24 Ripple Wall Tile	11-3/4" x 23-3/4" (29.92 cm x 60.43 cm)	5/16"	15.56	8
	2 x 4 Trapezoid Mosaic (Mesh-mounted)	12-1/4" x 11-1/8" Sheet (31.11 cm x 28.25 cm Sheet)	5/16"	9.50	10

TRIM

Description	Number	Size	Shape
Floor Bullnose	P43F9	3 x 24	
Cove Base	P36C9	6 x 12	
Cove Base Outcorner	PC36C9	1 x 6	
Jolly	S1/212J	1/2 x 12	

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	■*
Wet & Level – Interior Floor	≥ 0.42	■*
Shower Floors - Standard Center Drain (Residential or Light Commercial)	≥ 0.42	■**
Shower Floors - Linear Drain	≥ 0.60	
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■*
Pool Linings	N/A	■**

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazziusa.com/DCOF.

APPLICATION NOTES:

Floor and mosaic tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Wall tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

* Floor and Mosaic tile only.

** Mosaic tile only.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor Tile: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%) Wall: 1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%) Mosaic: 1/8"	Random Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor & Mosaic Result	Wall Result
Water Absorption	C373	< 0.5%	< 20.0%
Breaking Strength	C648	> 275 lbs	120 - 230 lbs
Scratch Hardness	MOHS	8.0	4.0 - 6.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at: marazziusa.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not use for ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazziusa.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazziusa.com/LargeTiles for more information.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

FEATURES

POST-CONSUMER RECYCLED MATERIALS

PRE-CONSUMER RECYCLED MATERIALS

MADE IN THE U.S.A.

REVEAL IMAGING®

CERTIFIED PORCELAIN TILE
 ZEROTOX
 Healthy Homes | Healthy Planet

All or select items within this series meet the requirements for these qualifications. For more information visit marazziusa.com.