

MARBLE OBSESSION™

COLORBODY™ AND GLAZED PORCELAIN FLOOR,
GLAZED CERAMIC WALL & MOSAICS

MARAZZI®

DARE TO BE BOLD™

MARBLE LOOK



MARBLE OBSESSION™

The pursuit of classic beauty and luxury is found within Marble Obsession™, a collection inspired by an array of three unique marble visuals. Its alluring color palette ranges from a classic white with dramatic gold veining to an attractive with grey featuring white striations. This well-rounded series offers versatility through a mix of different shapes, sizes, and finishes. Transcend traditional marble installations and step into the next level of marble-inspired designs with a 2x5 Picket mosaic, 8" Hex, and a 6" Arabesque wall piece, designed to mesmerize and satisfy your desire for modern elegance.



Cover photo features Marble Obsession™ Calacatta Gold, 12 x 24 on the floor and Predella™ Lumen White, River Pebble Mosaic Mix on the back wall.

Above photo features Grigio™, 12 x 24 on the wall, 24 x 24 on the floor and 2 x 5 Picket on the backsplash and inset.

MARBLE LOOK

FINISHES: MATTE | POLISHED | SATIN



MARBLE LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

COLORBODY™ PORCELAIN FLOOR TILE



MB20 Arabescato



MB21 Calacatta Gold



MB22 Grigio

GLAZED PORCELAIN 8" HEXAGON FLOOR TILE



MB20 Arabescato

MB21 Calacatta Gold

MB22 Grigio

GLAZED CERAMIC 6" ARABESQUE WALL TILE



MB20 Arabescato

MB21 Calacatta Gold

MB22 Grigio

GLAZED CERAMIC 2" x 5" PICKET MOSAIC TILE



MB20 Arabescato

MB21 Calacatta Gold

MB22 Grigio

GLAZED CERAMIC 2" x 2" MOSAIC TILE



MB20 Arabescato

MB21 Calacatta Gold

MB22 Grigio



VISIT MARAZZIUSA.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE | POLISHED | SATIN

USAGE

FLOOR

WALL

COUNTERTOP

SHOWER FLOOR

EXTERIOR FLOOR

MATERIAL

PC

PG

CG

PRICING

LOW

HIGH

SPECIAL FEATURES

STEPWISE™

TRUEEDGE™

REVEAL SYNC®

MADE IN THE U.S.A.

LARGE FORMAT

MOSAIC/DECO

ENCAUSTIC

TERRAZZO

PAVER

CUSTOMIZE

MARBLE LOOK

SIZES

			Thickness	Finish	Made in U.S.A.
	24 x 24 Floor Tile	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	5/16"	M P	
	12 x 24 Floor Tile	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	5/16"	M P	
	8" Hexagon Floor Tile	7-7/8" x 9-1/16" (19.95 cm x 23.04 cm)	5/16"	M	
	6" Arabesque Wall Tile	5-1/4" x 6" (13.33 cm x 15.24 cm)	5/16"	M	
	2 x 5 Picket Mosaic Tile (Dot-mounted)	12-1/4" x 11-1/8" Sheet (31.11 cm x 28.25 cm Sheet)	1/4"	S	
	2 x 2 Mosaic Tile (Dot-mounted)	12" x 12" Sheet (30.48 cm x 30.48 cm Sheet)	1/4"	M	

M Matte Finish P Polished Finish S Satin Finish

TRIM

Description	Number	Size	Shape	Finish
Floor Bullnose	P43F9	3 x 24		M P
Jolly	S1/212J	1/2 x 12		M

M Matte Finish P Polished Finish

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	■*
Wet & Level – Interior Floor	≥ 0.42	■**
Shower Floors – Standard Center Drain	≥ 0.42	■***
Shower Floors – Linear Drain	≥ 0.42 (Mosaic)	■***
	≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■*
Countertops	N/A	■*
Pool Linings	N/A	■*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazziusa.com/DCOF.

APPLICATION NOTES:

Floor Tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Wall and mosaic tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

- * Floor and mosaic tile only.
- ** Matte Floor and 2 x 2 mosaic tile only.
- *** 2 x 2 Mosaic tile only.
- ♦ Mosaic tile only.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor Tile: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%) Wall Tile: 1/16" Mosaic Tile: 1/8" 8" Hex: 3/16"	High Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%
Breaking Strength	C648	> 275 lbf	> 120 - 230 lbf	> 250 lbf
Scratch Hardness	C1895	8.0 (Matte) 6.0 (Polished)	4.0 - 6.0	8.0 (Matte) 6.0 (Satin)
Chemical Resistance	C650	Resistant	Resistant	Resistant

For additional information on test results, visit us at: marazziusa.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazziusa.com/Factors.

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazziusa.com/LargeTiles for more information.

Manufacturer Advisory: All tile is measured by the DCOF AcuTest™ method. Tiles with DCOF values <0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at www.tileusa.com.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

FEATURES

PRE-CONSUMER RECYCLED MATERIALS

POST-CONSUMER RECYCLED MATERIALS

REVEAL IMAGING®

CERTIFIED PORCELAIN

ZERO T^{OX}

All or select items within this series meet the requirements for these qualifications. For more information visit marazziusa.com.

© 2025 Marazzi (05/25)