

FINISHES: MATTE | LIGHT POLISHED | TEXTURED

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



STONE LOOK

## COLORBODY™ PORCELAIN FLOOR TILE



**MF01** Peak White



**MF02** Overland Beige



**MF03** Canyon Taupe



**MF04** Headland Fog



**MF05** Smoky Ridge

## MIXED CHEVRON MOSAIC 12 x 12 SHEET



**MF01** Peak White



**MF02** Overland Beige



**MF03** Canyon Taupe



**MF04** Headland Fog



**MF05** Smoky Ridge

## 2 x 2 MOSAIC - MATTE 12 x 12 SHEET



**MF01** Peak White\*

## 12 X 24 - TEXTURED WITH STEPWISE™ TECHNOLOGY



**MF01** Peak White\*

\*Available in all colors.



VISIT [MARAZZIUSA.COM/WHYTILE](http://MARAZZIUSA.COM/WHYTILE) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE | LIGHT POLISHED | TEXTURED

USAGE: FLOOR, WALL, COUNTERTOP, SHOWER FLOOR, EXTERIOR FLOOR

MATERIAL: PC PORCELAIN

PRICING: LOW, HIGH

SPECIAL FEATURES: STEPWISE™, TRUEEDGE™, MADE IN THE U.S.A., LARGE FORMAT

MOSAIC/DECO, ENCAUSTIC, ENCAUSTIC, PAVER, CUSTOMIZE

STONE LOOK

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 48 Floor Tile	23-3/8" x 46-15/16" (59.44 cm x 119.30 cm)	5/16"	15.26	2
	24 x 24 Floor Tile	23-3/8" x 23-3/8" (59.44 cm x 59.44 cm)	5/16"	15.20	4
	12 x 24* Floor Tile	11-5/8" x 23-3/8" (29.56 cm x 59.44 cm)	5/16"	17.02	9
	2 x 2 Mosaic - Matte <sup>■</sup> (Mesh-mounted)	(12" x 12" Sheet) (30.48 cm x 30.48 cm Sheet)	5/16"	10.00	10
	Mixed Chevron Mosaic <sup>◇</sup> (Mesh-mounted)	(12" x 13" Sheet) (30.48 cm x 33.02 cm Sheet)	5/16"	9.30	10

\* Also available in Textured finish with Stepwise™ Technology  
<sup>■</sup> Available in Matte only  
<sup>◇</sup> Available in a mix of Light Polished, Matte and Textured finishes

## TRIM

Description	Number	Size	Shape
Floor Bullnose*	P43F9	3 x 24	
Cove Base	P36C9T	6 x 12	
Cove Base Outcorner	PC36C9T	1 x 6	

\*Available in Matte and Light Polished  
 Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	■
Wet & Level – Interior Floor	≥ 0.42	■*
Shower Floors (Residential or Light Commercial)	≥ 0.42	■**
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	■***
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	■**

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [marazziusa.com/DCOF](http://marazziusa.com/DCOF).

### APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

\* Matte and Textured Floor tile and 2 x 2 Mosaic tile only.  
 \*\* 2 x 2 Mosaic tile only.  
 \*\*\* 12 x 24 Textured Floor tile with Stepwise™ Technology only.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor Tile: 1/8" (3/16" when multiple sizes are installed in a modular pattern, and/or when installing tile with a length 15" or greater in a staggered brick-joint pattern; overlap should not exceed 33%) Mosaic: 1/8"	High Variation

## PERFORMANCE CHARACTERISTICS

	ASTM#	Floor/Mosaic Results
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [marazziusa.com/information/TestResults](http://marazziusa.com/information/TestResults).

## DURABILITY

### Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [marazziusa.com/Factors](http://marazziusa.com/Factors)

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [marazziusa.com/LargeTiles](http://marazziusa.com/LargeTiles) for more information.

Manufacturer Advisory: All tile is measured by the DCOF AcuTest™ method. Tiles with DCOF values <0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A137.1 section 6.2.2.1.10, available at [www.tileusa.com](http://www.tileusa.com).

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

## FEATURES

PRE-CONSUMER RECYCLED MATERIALS

MADE IN THE U.S.A.

REVEAL IMAGING®

CERTIFIED PORCELAIN™

ZERO TOX™

All or select items within this series meet the requirements for these qualifications. For more information visit [marazziusa.com](http://marazziusa.com).