

# MODERN OASIS™

GLAZED PORCELAIN AND GLAZED CERAMIC MOSAICS

**MARAZZI**   
DARE TO BE BOLD™

STONE LOOK



# MODERN OASIS™

Monochromatic shadings and texture resembling windswept sand dunes define the contemporary limestone vibe of MODERN OASIS™. Rich, realistic graphic variations – linear to swirl – effortlessly flow from piece to piece in calming, organic shades. Dual-sized porcelain planks with flat surfaces, clean, straight edges and a controlled, neutral palette juxtapose strikingly with bolder elements of wood, glass and stone.



COVER PHOTO: STORMY SKY  
ABOVE PHOTO: SOFT CLOUD

STONE LOOK

FINISHES: MATTE

<b>USAGE</b>			<b>MATERIAL</b>		<b>PRICING</b>	<b>SPECIAL FEATURES</b>											
FLOOR	WALL	COUNTERTOP	SHOWER FLOOR	EXTERIOR FLOOR	CG	PG	LOW	HIGH	STEPWISE™	TRUEDGE™	MADE IN THE U.S.A.	LARGE FORMAT	MOSAIC/ DECO	ENCAUSTIC	TERRAZZO	PAVER	CUSTOMIZE

STONE LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

## 12 x 24 FLOOR TILE



**MD05** Soft Cloud



**MD06** Morning Haze



**MD09** Stormy Sky

## 24 x 24 FLOOR TILE



**MD05** Soft Cloud




**MD06** Morning Haze



**MD09** Stormy Sky


## 1 x 3 STACKED MOSAIC 12 x 12 SHEET



**MD05** Soft Cloud



**MD06** Morning Haze



**MD09** Stormy Sky

## 2 x 2 MOSAIC 12 x 12 SHEET



**MD05** Soft Cloud



**MD06** Morning Haze



**MD09** Stormy Sky



VISIT [MARAZZIUSA.COM/WHYTILE](http://MARAZZIUSA.COM/WHYTILE) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE

<b>USAGE</b>	<b>MATERIAL</b>	<b>PRICING</b>	<b>SPECIAL FEATURES</b>

STONE LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

## SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	24 x 24 Floor Tile	23-13/16" x 23-13/16" (60.48 cm x 60.48 cm)	5/16"	15.76	4
	12 x 24 Floor Tile	11-7/8" x 23-5/8" (30.23 cm x 60.12 cm)	5/16"	17.60	9
	1 x 3* Stacked Mosaic (Dot-mounted)	12-1/8" x 12-1/8" Sheet (30.80 cm x 30.80 cm)	1/4"	10.20	10
	2 x 2* Square Mosaic (Dot-mounted)	12" x 12" Sheet (30.48 cm x 30.48 cm)	1/4"	10.00	10

\*Glazed Ceramic Body

## TRIM

Description	Number	Size	Shape
Floor Bullnose	P43C9	3 x 12	
Cove Base	P36C9	6 x 12	
Cove Base Outcorner	PC36C9	6 x 1	

Cove base trim is intended to coordinate with floor tile in the standard 90-degree installation position.

## APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	■
Wet & Level – Interior Floor	≥ 0.42	■
Shower Floors - Standard Center Drain (Residential or Light Commercial)	≥ 0.42	■*
Shower Floors - Linear drain	≥ 0.60	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	■*

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [marazziusa.com/DCOF](http://marazziusa.com/DCOF).

### APPLICATION NOTES:

Floor tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

Mosaic tile suitable for exterior applications (provided it is noted as suitable in the applications chart above) in non-freezing climates, when proper installation methods are followed.

\* Mosaic tile only.

## INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor Tile: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern. When multiple sizes are installed in a modular pattern, please specify same size caliber at time of order.)  Mosaic: 1/8"	High Variation

## PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 3.0%
Breaking Strength	C648	> 275 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	8.0
Chemical Resistance	C650	Resistant	Resistant

For additional information on test results, visit us at: [marazziusa.com/information/TestResults](http://marazziusa.com/information/TestResults).

## DURABILITY

### Floor Surface Wear Resistance

1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

## NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: [marazziusa.com/Factors](http://marazziusa.com/Factors).

To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [marazziusa.com/LargeTiles](http://marazziusa.com/LargeTiles) for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit [marazziusa.com](http://marazziusa.com).

## FEATURES

POST-CONSUMER RECYCLED MATERIALS	PRE-CONSUMER RECYCLED MATERIALS
MADE IN THE U.S.A.	REVEAL IMAGING®

CERTIFIED PORCELAIN  
www.marazziusa.com



ZEROTOX  
Healthy. Noticed. Healthy Planet.

All or select items within this series meet the requirements for these qualifications. For more information visit [marazziusa.com](http://marazziusa.com).