RICE™

GLAZED PORCELAIN

MARAZZI®

DARE TO BE BOLD™

WALL



RICE™

Rice™ evokes the essence of handmade tile with its purposefully uneven surfaces and glossy finish. A neutral palette of Bianco, Natural, and Grigio, with undertones of Blu, comes in modular 6x6, 3x8 and 2x6 sizes and features straight edges. The integration of nature-inspired decos with four solid colors allows for customized installation patterns with distinct personalities, perfect for creating an intriguing visual with striking variation and depth.



Cover photo features Rice™ Natural, 6 x 6 Deco Blossom on the back wall and Marble Obsession™ Calacatta Gold, 12 x 24 on the floor.
Above photo features Rice™ Blu, 2 x 6 Deco Leaf on the wall and counter and Modern Formation™ Peak White, 12 x 24.

RICE™
GLAZED PORCELAIN

MARAZZI®
DARE TO BE BOLD™

FINISHES: GLOSSY

USAGE: FLOOR | WALL | COUNTERTOP | SHOWER FLOOR | EXTERIOR FLOOR

MATERIAL: PG GLAZED PORCELAIN

PRICING: LOW – HIGH

SPECIAL FEATURES: STEPWISE™ | TRUEDGE™ | REVEAL SYNCED™ | MADE IN THE U.S.A. | LARGE FORMAT | MOSAIC/DECO | ENCAUSTIC | TERRAZZO | PAVER | CUSTOMIZE

WALL

SEE CHARTS FOR FULL PRODUCT DETAILS.

2 x 6 WALL TILE



RC20 Bianco



RC21 Natural



RC23 Grigio



RC24 Blu

2 x 9 WALL TILE




RC20 Bianco



RC21 Natural



RC23 Grigio



RC24 Blu

3 x 8 WALL TILE



RC20 Bianco



RC21 Natural



RC23 Grigio



RC24 Blu

2 x 6 DECO LEAF TILE



RC50 Bianco



RC51 Natural



RC53 Grigio



RC54 Blu

6 x 6 DECO BLOSSOM



RC30 Bianco



RC31 Natural



RC33 Grigio



RC34 Blu

3 x 8 STRUCTURED WALL TILE



RC40 Bianco



RC41 Natural



RC43 Grigio



RC44 Blu

WATERPROOF | STAINPROOF | DENTPROOF | FIRE-RESISTANT | CLIMATEPRO™ | SIMPLICLEAN™

VISIT MARAZZIUSA.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

RICE™
GLAZED PORCELAIN

MARAZZI®
DARE TO BE BOLD™

FINISHES: GLOSSY

USAGE: FLOOR | WALL | COUNTERTOP | SHOWER FLOOR | EXTERIOR FLOOR
MATERIAL: PG GLAZED PORCELAIN
PRICING: LOW – HIGH
SPECIAL FEATURES: STEPWISE™ | TRUEDGE™ | REVEAL SYNCED™ | MADE IN THE U.S.A. | LARGE FORMAT | MOSAIC/DECO | ENCAUSTIC | TERRAZZO | PAVER | CUSTOMIZE

WALL

SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

		Thickness	Finish
6 x 6 Wall Tile	5-7/8" x 5-7/8" (15.00 cm x 15.00 cm)	3/8"	G
6 x 6 Wall Tile Deco	5-7/8" x 5-7/8" (15.00 cm x 15.00 cm)	3/8"	G
3 x 8 Wall Tile	2-15/16" x 7-7/8" (7.50 cm x 20.00 cm)	3/8"	G
3 x 8 Structured Wall Tile	2-15/16" x 7-7/8" (7.50 cm x 20.00 cm)	1/2"	G
2 x 9 Wall Tile	2-1/4 X 9-1/2 (5.71cm x 24.13cm)	3/8"	G
2 x 6 Wall Tile	1-15/16" x 5-7/8" (5.00 cm x 15.00 cm)	3/8"	G
2 x 6 Wall Tile Deco	1-15/16" x 5-7/8" (5.00 cm x 15.00 cm)	3/8"	G

G Glossy Finish

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors – Standard Center Drain	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■*
Pool Linings	N/A	■

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazziusa.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

* 6 x 6, 3 x 8, and 2 x 9 wall and deco tile only.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/16" (When rectangular size is installed in a staggered brick-joint pattern, overlap should not exceed 33%.)	V2 Medium Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	≥ 275 lbf
Scratch Hardness	C1895	7.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: marazziusa.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: marazziusa.com/Factors.

Use of a latex modified thin-set is recommended for installation. For more information, visit marazziusa.com.

FEATURES

PRE-CONSUMER RECYCLED MATERIALS

REVEAL IMAGING®

CERTIFIED PORCELAIN TILE | ZEROTOX

All or select items within this series meet the requirements for these qualifications. For more information visit marazziusa.com.

© 2026 Marazzi (08/26)