

RICE™  
GLAZED PORCELAIN

MARAZZI®  
DARE TO BE BOLD™

WALL





# RICE™

Rice™ evokes the essence of handmade tile with its purposefully uneven surfaces and glossy finish. A neutral palette of Bianco, Natural, and Grigio, with undertones of Blu, comes in modular 6x6, 3x8 and 2x6 sizes and features straight edges. The integration of nature-inspired decos with four solid colors allows for customized installation patterns with distinct personalities, perfect for creating an intriguing visual with striking variation and depth.



Cover photo features Bianco, 2 x 6 and Bianco Deco Leaf, 2 x 6 on the wall.  
Above photo features Rice™ Blu Structured, 3 x 8 on the walls and  
Scenario™ Nero Triangle, 8 x 8 on the floor.

WALL



FINISHES: GLOSSY

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



SEE CHARTS FOR FULL PRODUCT DETAILS.

WALL


**2 x 6 WALL TILE**



**RC20** Bianco



**RC21** Natural




**RC23** Grigio




**RC24** Blu

**3 x 8 WALL TILE**



**RC20** Bianco



**RC21** Natural




**RC23** Grigio



**RC24** Blu

**6 x 6 WALL TILE**




**RC20** Bianco



**RC21** Natural



**RC23** Grigio



**RC24** Blu

**6 x 6 DECO BLOSSOM**



**RC30** Bianco



**RC31** Natural



**RC33** Grigio



**RC34** Blu

**2 x 6 DECO LEAF**



**RC50** Bianco



**RC51** Natural




**RC53** Grigio




**RC54** Blu


**3 x 8 STRUCTURED WALL TILE**



**RC40** Bianco



**RC41** Natural



**RC43** Grigio



**RC44** Blu



WATERPROOF



STAINPROOF



DENTPROOF



FIRE-RESISTANT



CLIMATEPROOF™



SIMPLICLEAN™

VISIT [MARAZZIUSA.COM/WHYTILE](http://MARAZZIUSA.COM/WHYTILE) FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: GLOSSY

USAGE

 FLOOR

 WALL

 COUNTERTOP

 SHOWER FLOOR

 EXTERIOR FLOOR

MATERIAL

 PG

PRICING

 LOW

 HIGH

SPECIAL FEATURES

 STEPWISE™

 TRUEEDGE™

 REVEAL SYNCRO™

 MADE IN THE U.S.A.

 LARGE FORMAT

 MOSAIC/DECO

 ENCAUSTIC

 TERRAZZO













 PAVER

 CUSTOMIZE

SEE CHARTS FOR FULL PRODUCT DETAILS.




WALL

SIZES

			Thickness	Finish
	6 x 6 Wall Tile	5-7/8" x 5-7/8" (15.00 cm x 15.00 cm)	3/8"	
	6 x 6 Wall Tile Deco	5-7/8" x 5-7/8" (15.00 cm x 15.00 cm)	3/8"	
	3 x 8 Wall Tile	2-15/16" x 7-7/8" (7.50 cm x 20.00 cm)	3/8"	
	3 x 8 Structured Wall Tile	2-15/16" x 7-7/8" (7.50 cm x 20.00 cm)	1/2"	
	2 x 6 Wall Tile	1-15/16" x 5-7/8" (5.00 cm x 15.00 cm)	3/8"	
	2 x 6 Wall Tile Deco	1-15/16" x 5-7/8" (5.00 cm x 15.00 cm)	3/8"	

 Matte Finish

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors – Standard Center Drain	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	 *
Pool Linings	N/A	


A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [marazziusa.com/DCOF](https://marazziusa.com/DCOF).

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

\* 6 x 6, 3 x 8, and 2 x 6 wall and deco tile only.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Wall Tile: 1/16" (When rectangular size is installed in a staggered brick-joint pattern, overlap should not exceed 33%.)	 V2 Medium Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Wall Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbf
Scratch Hardness	C1895	7.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: [marazziusa.com/information/TestResults](https://marazziusa.com/information/TestResults).

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: [marazziusa.com/Factors..](https://marazziusa.com/Factors..)

Use of a latex modified thin-set is recommended for installation.  
For more information, visit [marazziusa.com](https://marazziusa.com).

FEATURES

 PRE-CONSUMER RECYCLED MATERIALS

 REVEAL IMAGING®

 CERTIFIED PORCELAIN TILE

 ZERO TO X

All or select items within this series meet the requirements for these qualifications. For more information visit [marazziusa.com](https://marazziusa.com).