

TREVERKSOUL™
GLAZED PORCELAIN

MARAZZI®
DARE TO BE BOLD™

WOOD LOOK



TREVERKSOUL™

Presenting an aristocratic soul with a contemporary feel, Treverksoul™ mimics realistic hardwood visuals combined with authentic knot and grainline variations. Inspired by antique parquet floors, this collection attractively revives a style from the past. Its distinct chevron shape filled with rich color and shade variation brings a refreshed ambiance to any space.



COVER PHOTO: NEUTRAL
ABOVE PHOTO: GREY

WOOD LOOK

FINISHES: MATTE

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



WOOD LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

FLOOR TILE



TR60 Neutral



TR61 Brown



TR62 Grey



VISIT MARAZZITILE.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

USAGE			MATERIAL		PRICING		SPECIAL FEATURES								
FLOOR	WALL	COUNTERTOP	SHOWER FLOOR	EXTERIOR FLOOR	PG	LOW HIGH	STEPWISE	TRUEDGE	MADE IN THE U.S.A.	LARGE FORMAT	MOSAIC/DECO	ENCAUSTIC	TERRAZZO	PAVER	CUSTOMIZE

WOOD LOOK

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	4 x 21 Floor Tile	4-5/16" x 21-1/4" (11.00 cm x 54.00 cm)	3/8"	10.12	18

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level - Interior Floor	N/A	■
Wet & Level - Interior Floor	≥ 0.42	■
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazzitile.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
Floor Tile: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern.)	Random Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: marazzitile.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	③	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazzitile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to marazzitile.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit marazzitile.com.

FEATURES

	PRE-CONSUMER RECYCLED MATERIALS		REVEAL IMAGING®
	CERTIFIED RECYCLED PORCELAIN TILE		ZEROTOX®

All or select items within this series meet the requirements for these qualifications. For more information visit marazzitile.com.