URBAN DISTRICT BRXTM







URBAN DISTRICT BRXTM



STONE LOOK

FINISHES: MATTE































SEE CHARTS FOR FULL PRODUCT DETAILS.

4 x 8 GLAZED PORCELAIN FLOOR TILE



UD01 Midtown



UD02 Industrial



UD03 Garden



UD05 Downtown



UD06 Eastside

2 x 8 GLAZED PORCELAIN FLOOR TILE



UD01 Midtown



UD02 Industrial



UD03 Garden



UD05 Downtown



UD06 Eastside















URBAN DISTRICT BRX™



FINISHES: MATTE





























STONE LOOK

SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

		Thickness	Finish
4 x 8 Floor Tile	4" x 7-15/16" (10.16 cm x 20.26 cm)	5/16"	M
2 x 8 Floor Tile	2-1/4" x 7-15/16" (5.65cm x 20.26cm)	5/16"	M



APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors – Standard Center Drain	≥ 0.42	
	≥ 0.42 (Mosaic)	
Shower Floors – Linear Drain	≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of \geq 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTestTM, visit marazziusa.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation	
3/16"	Random Variation	

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbf
Scratch Hardness	C1895	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: marazziusa.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	4	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazziusa.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Use of a latex modified thin-set is recommended for installation. For more information, visit marazziusa.com.

FEATURES



PRE-CONSUMER RECYCLED MATERIALS



POST-CONSUMER RECYCLED MATERIALS



REVEAL IMAGING®





All or select items within this series meet the requirements for these qualifications. For more information visit marazziusa.com.