

URBAN DISTRICT BRX™
GLAZED PORCELAIN

MARAZZI

DARE TO BE BOLD™

STONE LOOK



URBAN DISTRICT BRX™

Urban District BRX™ [bricks] is influenced by the hand-crafted shapes and highly variegated color expanses of nineteenth century Chicago brick heritage. Reclaimed. Revitalized. Remarkable. This bold new take on traditional brick uses modern ceramic technology to recreate the characteristics of artisanal masonry in a slim profile with a wide range of color-blends. BRX 2"x 8" and 4"x 8" modules easily accommodate basket weave, herringbone, stack and running-bond patterns in industrial, contemporary or traditional design settings.



DARE TO BE BOLD



WITH MARAZZI DESIGNS

COVER PHOTO: DOWNTOWN
ABOVE PHOTO: EASTSIDE

STONE LOOK

URBAN DISTRICT BRX™

GLAZED PORCELAIN

MARAZZI 
DARE TO BE BOLD™

FINISHES: MATTE

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



STONE LOOK

SEE CHARTS FOR FULL PRODUCT DETAILS.

4 x 8 GLAZED PORCELAIN TILE



UD01 Midtown



UD02 Industrial



UD03 Garden



UD06 Eastside




UD05 Downtown

2 x 8 GLAZED PORCELAIN TILE



UD01 Midtown



UD02 Industrial



UD03 Garden



UD06 Eastside



UD05 Downtown



VISIT MARAZZIUSA.COM/WHYTILE FOR A COMPLETE LIST OF QUALIFICATIONS AND EXCLUSIONS.

FINISHES: MATTE

USAGE



MATERIAL



PRICING



SPECIAL FEATURES



STONE LOOK

SEE CHARTS FOR FULL PRODUCT DETAILS.

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	4 x 8 Floor Tile	4" x 7-15/16" (10.16 cm x 20.26 cm)	3/8"	7.92	36
	2 x 8 Floor Tile	2" x 7-15/16" (5.08 cm x 20.26 cm)	3/8"	4.00	36

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	■
Wet & Level – Interior Floor	≥ 0.42	■
Shower Floors Standard Center Drain (Residential or Light Commercial)	≥ 0.42	
Shower Floors - Linear Drain	≥ 0.60	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	■
Countertops	N/A	■
Pool Linings	N/A	■

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3. For more information about DCOF and the DCOF AcuTest™, visit marazziusa.com/DCOF.

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16"	Random Variation

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant

For additional information on test results, visit us at: marazziusa.com/information/TestResults.

DURABILITY

Floor Surface Wear Resistance

1	Residential Bathrooms	3	All Residential / Light Commercial
2	All Residential Areas	④	All Residential / Commercial

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: marazziusa.com/Factors.

Random visuals enhance the natural beauty of this product. To achieve optimal results, all tile should be selected from multiple cartons and shading and graphic arrangement planned prior to installation.

Use of a latex modified thin-set is recommended for installation. For more information, visit marazziusa.com.

FEATURES

PRE-CONSUMER RECYCLED MATERIALS

REVEAL IMAGING®

POST-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information visit marazziusa.com.

