

SHOWER WALL PROGRAM



PANORAMIC PORCELAIN SURFACES™ PROVIDES GREATER EASE OF INSTALLATION WITH SHOWER WALLS AND TUB SURROUNDS.

SLAB | ELEMENTAL SELECTION



OPALITE CM55
6mm – Glossy | 48 x 96
Bookmatch available



STATUARIO CM03
6mm – Glossy | 48 x 96
Bookmatch available



DIAMOND MINE CM12
6mm – Glossy | 48 x 96
Bookmatch available
*Coordinates with Panoramic Duet™ Tile Series



GYPSUM CALACATTA CM22
6mm – Glossy | 48 x 96
Bookmatch available



SELENITE CM51
6mm – Matte | 48 x 96



LEMURIAN CM49
6mm – Glossy
32 x 72, 32 x 90, 36 x 90 & 48 x 96
Infinity Veining in 32 x 72, 32 x 90 & 36 x 90
Bookmatch available in 48 x 96 size only



AURALINE CM90
6mm – Glossy
32 x 72, 32 x 90 & 36 x 90
Infinity Veining



PEONY HS04
6mm – Honed
32 x 72, 32 x 90 & 36 x 90
Vein-cut
*Coordinates with Haddonstone™ Tile Series



DAWN HS05
6mm – Honed
32 x 72, 32 x 90 & 36 x 90
Vein-cut
*Coordinates with Haddonstone™ Tile Series



HORIZON HS07
6mm – Honed
32 x 72, 32 x 90 & 36 x 90
Vein-cut
*Coordinates with Haddonstone™ Tile Series

Bookmatch: Slabs are crafted to create a mirrored pattern, offering a stunning symmetrical appearance in installations.

Infinity Veining: Slabs feature a continuous pattern, providing installations with a seamless and uninterrupted look

*Tile coordination available for a complete bathroom design solution.



In addition to reducing the amount of waste generated during installation, these sizes contribute to a more seamless process. Featuring a curated selection of our most popular colors alongside new designs, the expanded formats are crafted to meet every need.

Note: 48 x 96 nominal size (47.2 x 94.5 actual size) | 32 x 72, 32 x 90, and 36 x 90 nominal sizes.



SCRATCH-RESISTANT



HIGHLY STAIN-RESISTANT



HIGH HEAT & FIRE-RESISTANT



NON-POUROUS / WATER & MOISTURE PROOF



CUSTOM FITTED



UNPARALLELED PERFORMANCE



ENGINEERED FOR CONSISTENCY

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓
Wet & Level – Interior Floor	≥ 0.42	✓*
Shower Floors – Standard Center Drain	≥ 0.42	
Shower Floors – Linear Drain	≥ 0.42 (Mosaic) ≥ 0.60 (Floor)	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	✓

A DCOF value of ≥0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A1371-A326.3. For more information about DCOF and the DCOF AcuTest™, visit [daltille.com/DCOF](http://daltile.com/DCOF).

APPLICATION NOTES:

Suitable for exterior applications (provided it is noted as suitable in the applications chart above) in freezing and non-freezing climates, when proper installation methods are followed.

*Matte and honed finishes only.

INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8"	High (V3)

FACE VARIATION

