



Vscan Air™ with Vscan Air SL probe

See more. Treat faster.



Table of contents

Vscan Air with Vscan Air SL probe.....	3
General characteristics	3
Sector array transducer for deep scanning.....	4
Linear array transducer for shallow scanning	4
Modes	5
Vscan Air image quality	5
User interface.....	5
Data storage.....	6
Patient data identification.....	6
Exam data on device.....	6
Data export.....	6
Supported DICOM services.....	6
Data security	6
Reporting.....	7
Findings Report.....	7
Digital tools and AI features	7
Caption AI	8
AutoAS	8
Lung Guidance	8
Bladder volume measurements	8
Display devices and operating system options.....	9
Standard configuration	9
Available accessories	9
User support tools	9
Vscan Support Center.....	9
Safety conformance	10
Safety classifications	10

Vscan Air with Vscan Air SL probe

Vscan Air is a battery-operated, general-purpose diagnostic ultrasound imaging system for use by qualified and trained healthcare professionals or practitioners. It enables ultrasound guidance as well as visualization and measurement of anatomical structures and fluid.

Vscan Air SL consists of a dual-headed probe model with sector array transducer on one end and linear array transducer on the other. It comes with an app which can be installed on Android™ or iOS® mobile devices.

Its pocket-sized portability and simplified user interface enable integration into training sessions and examinations in professional healthcare facilities (ex. hospital, clinic, medical office), home environments, road/air ambulance, and other environments described in the product user manual. The information can be used for basic, focused assessments and adjunctively with other medical data for clinical diagnosis purposes during routine, periodic follow-up, and triage assessments for adult, pediatric, and neonatal patients. Vscan Air can also be useful for interventional guidance.

The Vscan Air website is available for accessing supplementary product and clinical information.

General characteristics

- 128 physical channel beamforming
- Total scan time of 50 minutes with fully charged battery (with 80% black and white, 20% color imaging)
- Harmonic imaging for increased signal-to-noise ratio and reduced artifacts from side lobes, grating lobes, and reverberations, resulting in superior tissue definition and reduced speckle artifacts. With the greater penetration of lower ultrasound frequencies, high-quality harmonic imaging at greater depth can be performed
- Recharge battery from 10% to 90% capacity in 75 minutes
- Start scanning faster with smart connect pairing, which keeps your probe connected to your display device while charging
- Dimension: 141 x 67 x 33 mm
- Weight: 218 ± 3 grams
- IP67-rated
- Drop robustness: MIL-STD-810G, Method 516.7, Table 516.7-7
- Storage mode enables you to store the probe up to 36 months without significant battery degradation





Sector array transducer for deep scanning

- XDClear™ transducer technology delivering high level of penetration, resolution, and sensitivity—enabling high-performance ultrasound for broad range of patients.
 - **Single Crystal** provides higher frequency bandwidth than traditional piezoelectric material, which can produce greater image uniformity and stronger penetration
 - **Acoustic Amplifier Architecture** provides a comprehensive acoustic insulation from mechanical structures and increased power efficiency bandwidth with reduced noise and less heat dissipation
 - **Cool Stack** relieves inherent heat via an embedded special material that has a high degree of thermal connectivity to further extend penetration and diagnostic power
- Specific clinical applications and exam types including: cardiac (adult and pediatric, 40 kg and above), abdominal, fetal/obstetric, gynecological, urological, thoracic/lung, pediatric, adult cephalic, interventional guidance (includes free-hand needle/catheter placement, fluid drainage, nerve block and biopsy)
- Broad-bandwidth sector array: 1.6 – 3.7 MHz with center frequency of 2.65 MHz
- Number of elements: 64
- Footprint: 22 mm x 17 mm (lens)
- Viewing angle: Up to 90°
- Depth: Up to 24 cm



Linear array transducer for shallow scanning

- Specific clinical applications and exam types including: vascular/peripheral vascular, musculoskeletal (conventional and superficial), small organs, thoracic/lung, ophthalmic, pediatric, neonatal cephalic, interventional guidance (includes free-hand needle/catheter placement, fluid drainage, nerve block, vascular access and biopsy)
- Broad-bandwidth linear array: 3 – 12 MHz with center frequency of 7.7 MHz
- Number of elements: 192
- Footprint: 40 mm x 7 mm (lens)
- Depth: Up to 8 cm



Modes



B-mode

Black/white imaging

- Black-and-white mode for displaying anatomy in two dimensions in real time



Color Doppler

Color flow

- Color-coded overlay for real-time blood flow imaging



PW

Pulsed wave spectral Doppler

- Displays speed and direction of blood flow allowing velocity measurements



M-mode

Motion mode

- Displays tissue motion over time (along one direction as indicated by M-mode cursor)

Vscan Air image quality

With our proprietary SignalMax™ + XDclear technology, GE HealthCare continues to challenge expectations regarding the limits of ultrasound image quality. We've set a new standard in handheld ultrasound by miniaturizing the power of XDclear to deliver extraordinary image quality with our sector phased array transducer. This combines the power of SignalMax high-intensity signal processing with industry-leading single crystal transducer technology for exceptional penetration, resolution and sensitivity in imaging performance.

Vscan Air also uses High-Definition Speckle Reduction Imaging* (HD-SRI) to give a boost to our already outstanding image quality. HD-SRI delivers improved image quality with optimized contrast resolution and a smoother appearance to enhance the details while maintaining the image's integrity.

User interface

Helps enhance ultrasound imaging with a minimized number of keys and intuitive, thumb-controllable, touchscreen user interface. The Vscan Air app supports portrait as well as landscape mode to optimize image size and ergonomics for different use scenarios.

- Single key/gesture to control freeze/unfreeze, store, gain, and depth control
- Two steps to change preset with appropriate transducer
- Two steps to start reviewing images from an exam
- Presets with optimized settings for imaging different organs. User-selectable default preset for immediate use after starting the app
- Measurements: Distance, circumference, area, angle, velocity, slope, heart rate, bladder volume and obstetric measurements (BPD, HC, AC, FL, CRL, AFI, DVP and AOP)
- Annotations: Arrow and free text
- Transducer element check
- Selectable centerline marker
- Selectable TGC control with 6 depth-dependent gain controls
- Device configuration and management tools are easily reachable by swiping in the menu
 - Enablement of TGC controls, preview mode, storage of binary images
 - Settings for auto-freeze, video duration
 - Configuration of probe button function (freeze or store)
 - Download user manual in selectable language to Vscan Air app
 - Diagnostics in Vscan Air app with ability to upload log files to GE HealthCare server
 - Direct access to customer support information
 - Information about software status of probe and app with ability to un- and re-register



Data storage

Patient data identification

- Manual data entry of patient information for an exam
- Select from DICOM® Modality Worklist on request. Such worklist supports consistent labeling of images, video clips, and exams before export to DICOM PACS
- Query DICOM Modality Worklist for a particular patient ID
- Barcode scanning is a Vscan Air app embedded feature which allows users to utilize their display device's rear camera to scan a barcode on wristbands, ID stickers, or requisition forms to initiate an MWL query. Requires a configured MWL server and rear camera permission.

Exam data on device

- Data for up to 500 exams can be stored on mobile device
- Data is stored in generic formats: jpg for still frames, mpg for videos
- Complementing storage of binary image data can be selected. Such data could be useful for further image analytics in collaboration with GE HealthCare
- Data is organized as individual examinations with a collection of images and can be linked with patient identification
- All stored data can be recalled for review

Data export

- Anonymized images and videos can be shared with other apps available on smart devices
- Images, video clips, or exams with or without patient information can be wirelessly exported in generic formats (jpg, mp4) to shared network folders
- Images, video clips, or exams with patient information can be wirelessly exported in DICOM format to DICOM PACS
- Images, video clips, or exams with patient information can be wirelessly exported in DICOMweb™ format using TLS protocol to Verisound™ Gallery¹ (option) or other compatible third-party cloud storage (STOW-RS)
- ATNA audit records using Syslog protocol

Supported DICOM services

- Verify
- Modality Worklist
- Store
- Storage Commitment
- Secure DICOM (TLS)
- Secure DICOMweb – STOW-RS (TLS)
- Modality Performance Procedure Step (MPPS)

Data security

Secured data at rest

- Vscan Air app starts only after confirmation of mobile device protection with user authentication
- Additional security provision via unique user accounts and password protection for the app
- Multiple users utilizing a shared mobile device can create and use their own account
- Account sign-in credentials support the integration of enterprise identity providers (IdP)¹ for enterprise Single Sign-On (SSO) user authentication
- Images and other patient information data are stored in a private, on-device space with no access from other apps on the mobile device
- Images are stored on-device without embedded patient identification and linked with encrypted patient database
- FIPS 140-2 compliant database encryption (AES-256-bit encryption)
- User-selectable, additional PIN or biometric (Face ID or fingerprint) protected access to patient data on Vscan Air app
- Exam data is wiped off the device after 10 attempts with incorrect PIN

Secured data on the move

- Images are anonymized before being shared with other apps on the mobile device
- Support of enterprise-grade wireless encryption standards including EAP and WPA2 (PSK)
- TLS encryption with optional peer authentication to support secure DICOM transfer
- Configurable time period for image removal on the device after confirmed storage from DICOM Storage Commitment server
- MyRemoteShare¹ calls are encrypted end to end (over TLS) (option)
- Image/Exam export to Verisound Gallery¹ is via secure DICOMweb transfer (STOW-RS over TLS) (option)

Secure authentication options

- Complex password authentication with automatic sign-out options or federated identity enterprise Single Sign-On (SSO)

SSO prerequisites:

- Public IP addresses: Federation servers should be accessible via a public IP address over the internet
- Firewall configuration: Open specific ports to allow federation traffic (e.g., ports 443 for HTTPS)
- Internet connection: A stable and reliable internet connection with sufficient bandwidth to handle the anticipated traffic

Software:

- Install necessary software (e.g., ADFS, Azure AD Connect) to support federation
- Data encryption: Ensure all data in transit is encrypted using TLS/SSL

Supported protocols:

- SAMLv2 (Strongly preferred)
- Open ID Connect (OIDC)/OAuth2.0 (Strongly preferred)
- Read-only Lightweight Active Directory Protocol (LDAPs) over a secure channel



Reporting

Findings Report^{1*}

The Findings Report on Vscan Air helps clinicians quickly capture and communicate key ultrasound exam results. It combines images, structured fields, and easy-to-use templates to support consistent bedside documentation with just a few taps.

- **Quick, guided reporting:** Document common findings and interpretations with streamlined templates designed for point of care use.
- **Easy report generation:** Create a nearly instant report from current selections to minimize time spent on documentation at the point of care.
- **Flexible data entry:** Use worksheets and open-choice fields to capture both standard and uncommon findings.
- **Easy export:** Save and share a clean, time-stamped image of the report.

Digital tools and AI features

Digital tools and AI features for Vscan Air are optional and may be sold separately from the device, either individually or as part of an offering bundle.



MyRemoteShare²

- Enables a Vscan Air user to engage in an audio conversation with a remote person while using the device to share the scan screen (video from the user's mobile device camera may also be shared)
- Remote participants can join a MyRemoteShare session via any standard web browser on a computer or mobile devices via a unique link
- MyRemoteShare is powered by Zoom's secure healthcare application



Verisound Gallery

- A cloud-based secure data storage and management solution for DICOM images and exams exported from a Vscan Air app
- Accessed by sign-in to myvscan.gehealthcare.com using the same credentials used for the Vscan Air app
- Review uploaded exams/images or share them with named peers or colleagues



MyDeviceHub


- A device management solution for enterprises to manage their fleet of Vscan Air devices
- Accessed by the organization's named administrators via myvscan.gehealthcare.com
- Ability to register Vscan Air probes in bulk, manage access to named users, and centrally configure DICOM servers






Caption AI™: Caption Guidance™ and Caption Interpretation™ AutoEF*

Vscan Air SL with Caption AI software provides real-time guidance that shows step-by-step, how to maneuver the probe to capture diagnostic-quality standard echocardiographic views. Once the relevant image(s) are acquired, a left ventricular ejection fraction is automatically calculated. Customizable indication-based or workflow-based protocols of cardiac ultrasound views are also available. Color Doppler views can be added to any protocol, and an auto-box placement feature assists with color box positioning.^{9**}




AutoAS^{†,^}

AutoAS provides an AI-assisted automated visual estimate of the presence or absence of moderate to severe aortic stenosis (AS) using standard 2D cardiac images. AutoAS is designed to evaluate the severity of AS to assist users in the early assessment of valve disease at the point of care. AutoAS analyzes B-mode cardiac ultrasound clips (PLAX, PSAX-AV, and AP5) previously acquired with Vscan Air SL and, with at least two compatible clips, provides an AI-generated estimate indicating whether findings are suggestive of moderate or severe AS. AutoAS also provides a confidence score that indicates how certain the algorithm is in its prediction.⁹




Lung Guidance*

Lung Guidance assists clinicians in acquiring lung ultrasound images by helping to identify key anatomical landmarks across a standard 8-zone lung protocol. The tool offers users guided image acquisition and hands-free auto capture for upper and lower anterior and lateral views. Lung Guidance on Vscan Air offers simple and consistent image capture for streamlined point of care lung assessments.⁹



Bladder volume measurements*

Bladder volume¹ is a protocol-based measurement tool for calculating urinary bladder volumes. When using the bladder volume protocol, the measurement calipers are placed at default positions that users can easily adjust. After acquiring the measurements from the transverse and longitudinal images, the bladder volume is calculated automatically.



Display devices and operating system options⁵

Operating system options

Android phones and tablets with OS version 14, 15, or 16. Devices with 0x64 ARM based CPU architecture and 64-bit Kernel, minimum 4 GB RAM, Android open GL ES 3.0, and compatibility with Google Play™ store

iPhone devices with iOS 17, 18 or 26

iPad devices with iPad iOS 17, 18 or 26

Screen requirements

Size: 5 to 20 inches

960 x 640 (or 640 x 960) pixels or more

Internal memory requirement

8 GB storage space

Connectivity requirements

IEEE 802.11n

Wi-Fi Direct (Android only)

5 GHz

Bluetooth® Low-Energy 4.0

Note: Some Android devices claim 5 GHz but may only support 2.4 GHz for Wi-Fi Direct, resulting in inability to connect to the probe. Currently observed on a few Sharp, Sony and Kyocera devices. 5 GHz is not forced in countries where only the 2.4 GHz band is available.

Security requirements

WPA2™

Data on device must be encrypted and authentication enabled

We highly recommend using a display device and OS that are verified/validated by GE HealthCare for compatibility with Vscan Air. The list of verified/validated devices can be found in Vscan Support Center.

Standard configuration

The following items are included in the standard Vscan Air offering

- Vscan Air SL probe
- Vscan Air app (Vscan Air for iOS and Vscan Air for Android)³
- Protective carrying case
- Wireless charger including USB cable
- Country-specific AC adapter⁴
- Quick Start Guide
- Electronic user manual

Available accessories

- User manual in different languages
- Additional protective carrying case
- Additional wireless charger including USB cable
- trophon® Wireless Ultrasound Probe Holder¹
- AC Adapter Multiplug¹
- Vscan Air Roll Stand¹

User support tools

Vscan Support Center

- Enhances the Vscan Air experience by providing online resources from product information to clinical and service support
- Additional educational resources will be posted on the Vscan Support Center website, including webinars, thought leadership, further online programs, and training opportunities



Safety conformance

Safety classifications

- Vscan Air SL probe is classified as internally powered medical electrical equipment with type BF applied parts according to IEC 60601-1⁶
- Vscan Air SL probe is CE-marked according to MDR (2017/745/EU), RED (2014/53/EU), RoHS (2015/863/EU), and is compliant to 2012/19/EU (WEEE)
- Vscan Air R3 for Android and Vscan Air R3 for iOS are CE-marked according to MDR (2017/745/EU)
- Vscan Air SL probe is NRTL Certified to CAN/CSA-C22.2 No. 60601-1 and ANSI/AAMI ES60601-1
- Wireless charger pad of Vscan Air is certified according to IEC/EN62368-1

Vscan Air conforms to applicable clauses of the following safety standards:

IEC 60601-1 ⁷	Medical electrical equipment — Part 1: General requirements for basic safety and essential performance
IEC 60601-1-2 ⁷	Medical electrical equipment — Part 1-2: General requirements for basic safety and essential performance — Collateral Standard: Electromagnetic disturbances — Requirements and tests (Group One, Class B per CISPR 11 / EN 55011)
IEC 60601-2-37	Medical electrical equipment — Part 2-37: Particular requirements for the basic safety and essential performance of ultrasonic medical diagnostic and monitoring equipment
IEC 60601-1-11	Medical electrical equipment — Part 1-11: General requirements for basic safety and essential performance — Collateral Standard: Requirements for medical electrical equipment and medical electrical systems used in the home healthcare environment
IEC 60601-1-12	Medical electrical equipment — Part 1-12: General requirements for basic safety and essential performance — Collateral Standard: Requirements for medical electrical equipment and medical electrical systems intended for use in the emergency medical services environment
EN 13718-1	Medical vehicles and their equipment — Air ambulances Part 1: Requirements for medical devices used in air ambulances
EN 1789	Medical vehicles and their equipment — Road ambulances
ISO 10993-1 ⁸	Biological evaluation of medical devices Part 1: Evaluation and testing within a risk management process
IEC 62304	Medical device software – Software life cycle processes
IEC 62366-1	Medical devices – Part 1: Application of usability engineering to medical devices
IEC 60601-1-6	Usability engineering collateral



1. Not available in every country.
2. The quality of the ultrasound image visible to the remote participant is dependent on the network connection and display device used by the participant, thus it cannot be validated. MyRemoteShare is therefore not intended for diagnostic purposes.
3. The Vscan Air app can be downloaded via App Store or Google Play, accordingly. It converts after confirmed by e-mail registration into a medical device. Before converting, it can be used for preview purposes as non-medical device.
4. In accordance to IEC classification for power plugs, one AC adapter with either an A, C, F, G, or I connector will be part of standard configuration.
5. Using the Vscan Air app with a mobile device which does not meet the minimum requirements may result in low-quality images, unexpected results and possible misdiagnosis. The Vscan Air app may not work in all devices. A recommended step in testing a particular device compatibility is the download, installation and first use of the Vscan Air app in preview mode.
6. When not charging using the wireless charger.
7. Including national deviations.
8. Includes compliance to relevant sub-parts of ISO 10993 as per the intended use of Vscan Air.
9. This feature is available on phone and tablets that have been verified and validated by GE HealthCare for compatibility. The list of compatible devices can be found at the Vscan Air Support Center website.

About GE HealthCare

About GE HealthCare Technologies Inc.

GE HealthCare is a leading global medical technology, pharmaceutical diagnostics, and digital solutions innovator, dedicated to providing integrated solutions, services, and data analytics to make hospitals more efficient, clinicians more effective, therapies more precise, and patients healthier and happier. Serving patients and providers for more than 125 years, GE HealthCare is advancing personalized, connected, and compassionate care, while simplifying the patient's journey across the care pathway. Together our Imaging, Ultrasound, Patient Care Solutions, and Pharmaceutical Diagnostics businesses help improve patient care from diagnosis, to therapy, to monitoring. We are a \$20.6 billion business with approximately 54,000 colleagues working to create a world where healthcare has no limits.

Follow us on [LinkedIn](#), [Facebook](#), [Instagram](#), and [Insights](#) for the latest news, or visit our website <https://www.gehealthcare.com/en> for more information.

*Non-standard option.

**Not AI-driven.

† The results of AutoAS are not intended to be used on a stand-alone basis for clinical decision-making and are not intended to supplement or replace a full echocardiogram examination.

^ Only available for images acquired using the sector transducer Cardiac preset or the Cardiac Guidance tool.

Product may not be available in all countries and regions. Full product technical specification is available upon request. Contact a GE HealthCare Representative for more information. Please visit <https://www.gehealthcare.com/en>.

Data subject to change.

© 2026 GE HealthCare. Vscan Air, Vscan, Verisound, SignalMax, Caption AI, Caption Guidance, Caption Interpretation, and XDclear are trademarks GE HealthCare. GE is a trademark of General Electric Company used under trademark license. Google, Android and Google Play are registered trademarks of Google LLC. DICOM and DICOMweb are registered trademarks of the National Electrical Manufacturers Association for its standards publications relating to digital communications of medical information. App Store is a trademark of Apple Inc., registered in the U.S. and other countries. IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license. The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. WPA and WPA2 a reregistered trademarks of Wi-Fi Alliance. All other third-party trademarks are the property of their respective owners.

April 2026

DOC3067867



GE HealthCare