

# Topgard® Protective Caps & Full Brim Hats

Technical Specifications



*Made of durable polycarbonate and featuring a uni-ridge design, these caps are designed for use by utilities and other industries where head protection with dielectric protection is necessary.*

⚙️ Topgard cap shown with Fas-Trac® III Suspension



## Features

- Superior top impact protection
- Tested to radiant heat loads producing temperatures up to, but not exceeding, 275°F
- Slotted cap designed for use with MSA accessories to ensure compliance with the helmet & accessory

## Markets

- Electric/utilities
- Oil, gas and petrochemical
- General industry and manufacturing
- Construction

## Customization

- 27+, factory applied reflective or retro-reflective stripes
- Multiple printing services: one-color logo to digital photos; up to four locations
- For additional details, visit [msasafety.com](http://msasafety.com) KEYWORD: logo

## Care & Maintenance

- Clean helmet assembly regularly with MSA's Confidence Plus Cleaning Solution (P/Ns 10009971 or 10032737) or mild soap (no detergents) and warm water
- Do not throw, drop, use as support or abuse helmet to ensure proper working condition
- Store helmet in clean, dry environment <49°C (120°F)

## Service Life Guidelines

- Topgard Helmets are made with high-quality, wear-resistant materials
- Inspect the helmet before and after each use and replace any part(s) as required
- Always replace the helmet after it has withstood an impact or penetration. MSA recommends:
  - replacing the suspension after no more than 12 months of use
  - replacing the shell after no more than five (5) years of use
- Please consult user instructions for additional details

Specifications	
<b>STANDARDS COMPLIANCE</b>	ANSI/ISEA Z89.1-2014 CSA Z94.1-2014
<b>CLASSIFICATION</b>	Type I, Class E
<b>CERTIFICATION</b>	Third-party by SEI
<b>APPLICATION(S)</b>	General Purpose; Elevated Temperatures
<b>PRODUCT SIZES</b>	Standard (6½" to 8")
<b>SHELL MATERIAL</b>	Polycarbonate with UV inhibitor
<b>AVAILABLE STYLES</b>	Slotted Cap Unslotted Full Brim Hat
<b>AVAILABLE SUSPENSIONS</b>	Fas-Trac® III Ratchet 1-Touch Slide Closure Swing Ratchet
<b>REQUIREMENTS FOR OPTIONAL FEATURES (Z89.1)</b>	Reverse Donning, Lower Temperature, Higher Temperature, Hi-Viz (as indicated)
<b>COLORS</b>	8 (stocked for caps) 4 (stocked for hats) Other colors available, including custom colors
<b>OTHER PPE</b>	MSA accessories (including lamp bracket/cord holder), MSA hearing protectors, V-Gard Face Protection System, Winter Liners and chinstraps
<b>PRODUCT DIMENSIONS</b>	
CAP	11.5" x 8.75" x 5.75", 0.74 lb
HAT	12.25" x 10.75" x 6.25", 0.88 lb
<b>MIN ORDER QUANTITIES (MOQ)</b>	20 (stocked colors) 100 (non-stocked colors) 500 (custom colors)
<b>SHIPPING CARTON DIMENSIONS (BOX OF 20)</b>	
CAP	22.5" x 18.25" x 14", 19.6 lb
HAT	25.1875" x 21.75" x 15.5", 22.4 lb

## Technical Assistance/Additional Information

For more information about Topgard Helmets and other MSA products, please contact MSA Customer Service at 1-800-MSA-2222 or visit [MSAsafety.com](http://MSAsafety.com).

**MSA – The Safety Company**  
1000 Cranberry Woods Drive  
Cranberry Township, PA 16066 USA  
Phone 724-776-8600  
[www.MSAsafety.com](http://www.MSAsafety.com)

**MSA Canada**  
Phone 1-800-672-2222  
Fax 1-800-967-0398

**U.S. Customer Service Center**  
Phone 1-800-MSA-2222  
Fax 1-800-967-0398