

MSA Workman® Mini PFL Product Specifications



FEATURES	BENEFITS
INTERNAL PAWL-LOCK	Provides many lower level tie-off points for numerous work applications
SWIVEL EYE CONNECTION	Eliminates line twisting
HIGH WEIGHT CAPACITY	Accommodates users up to 400 lbs.
TWIN-LEG CARABINER CONNECTION	Keeps harness D-ring available for use with other equipment while climbing, or for rescue purposes

PERFORMANCE SPECIFICATIONS	
TENSILE STRENGTH	(US) 3,000 lb. minimum; (EU) 3,372 lb. minimum
MAXIMUM CAPACITY	(US) 400 lbs.; (EU) 310 lbs.
MAXIMUM ARREST DISTANCE	(US) 24 inches
AVERAGE ARREST FORCE	≤ 900 lbs. (ANSI Z359.14)

MATERIAL SPECIFICATIONS	
WEIGHT	1.78 lbs. (w/o snaphook)
UNIT LENGTH	13 inches
UNIT WIDTH	3.93 inches
UNIT DEPTH	2.12 inches
UNIT HOUSING	Polycarbonate
LIFELINE MATERIAL	Nylon
LIFELINE LENGTH	6 ft., standard; 9 ft., tie-back version

APPROVALS	
ANSI Z359.14, Class A	EN 360:2002
CSA Z259.2.2	ABNT NBR 14628
OSHA	GB 24544-2009

For More Information

- MSAsafety.com
- [facebook.com/MSAsafety](https://www.facebook.com/MSAsafety)
- 1-800-MSA-2222
- twitter.com/MSAsafety
- info@MSAsafety.com
- [youtube.com/MSAsafety](https://www.youtube.com/MSAsafety)



Workman Mini PFL Single-leg with Carabiner
Part No. 10157844



Workman Mini PFL Twin-leg with Carabiner
Part No. 10157862



Workman Mini PFL Twin-leg with Tie-back™
Part No. 10157864