

# **Technical Information Sheet**

**3M<sup>TM</sup> Low-Profile Fastener Systems** 

#7336, Low-Profile Polyolefin Hook Fastener with High-Tack Medical Adhesive [MSX-6981]

Effective Date: January 2015

Supersedes all previous information sheets

## **Current Product Description:**

#7336 is a white polyolefin hook fastener backed with a very high adhesion, synthetic rubber-based adhesive designed for medical device construction and applications that require high peel strength.

#### **Features and Benefits:**

- Aggressive Adhesion to Films & Nonwovens - EtO Sterilization Compatible

- Medical Device Construction & Closures - Thin and Conformable

- Limited Gamma Exposure - <45kGrays

- No Natural Rubber Latex

# **Composition:**

Low Profile Hook	White Polyolefin Copolymer Microreplicated Hook	
Adhesive	Synthetic rubber system, 3M Proprietary, designed for medical	
	use	
Release Liner	3.5 mil (0.09 mm) 63 lb. Bleached Kraft Paper, silicone-coated	
Tape Thickness, no liner	19 mils (0.5 mm) typical	

# Properties<sup>1</sup>:

135 Degree Peel, Average <sup>2</sup>	~ 12.5 oz/inch width (360 g/25 mm width)
Dynamic Shear Closure, Average <sup>2</sup>	~ 290 oz/0.5 inch <sup>2</sup> (8.3 kg/3.25 cm <sup>2</sup> )
Adhesion to S. Steel, 180 Degree Peel	80 oz/inch width (2.27 kg/25 mm)(22.2 N/25mm)
Liner Release, Maximum	60 gm/inch width (60 gm/25 mm width)
Maximum Roll Length & Width	Width – 26 inches (66 cm)
Transmission and a configuration of the configurati	Length – 145 yards (~132 meters)

<sup>&</sup>lt;sup>1</sup> Properties listed based on limited data and subject to change.

## **Shelf Life and Storage Conditions:**

Product as supplied in original packaging will maintain stated properties for a period of two [2] years from date stamped on shipping container when stored at temperatures between 50-80°F (10-27°C) and relative humidity between 40-60 percent.

Please see reverse side for important product, safety and warranty information.

<sup>&</sup>lt;sup>2</sup> Peel and shear tested used 3M #7330 Loop, are based on limited data and subject to change

**Product and Safety Information:** User is solely responsible for determining the suitability of 3M samples and products for the intended use including any necessary safety or toxicity assessment. 3M will provide Material Safety Data Sheets and results of toxicity testing upon request. In every case before using any product in full scale production users should conduct their own tests to determine to their own satisfaction whether the product is of acceptable quality and is suitable for their particular purposes under their own operating conditions.

Notice: Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendations to practice any invention covered by any patent, without authority from the owners of this patent.

#### Warranty Information

All statements, technical information and recommendations herein are based on tests 3M believes to be reliable, but the accuracy or completeness thereof is not guaranteed. 3M warrants only that products will meet 3M's specifications at the time of shipment to the customer. 3M does not offer any other warranty and does not warrant the performance, safety or such other characteristics of Products in combination with other materials. 3M specifically DOES NOT warrant Products for any intended or unintended uses (whether or not foreseeable); for compatibility or suitability with other components or compatibility with any methods of manufacture or conversion. The foregoing warranty is made in lieu of all other warranties, expressed or implied, including the implied warranties of merchantability, fitness for a particular purpose and freedom from non-infringement.

**Limitation of Remedies:** If products are proven not to meet 3M's specifications, the sole and exclusive remedy available and 3M's only obligation shall be, at 3M's option, to replace such quantity of Products which are proven out of specification or to refund the purchase price paid for Products.

Limitations of Liabilities: The remedies provided herein are exclusive remedies against 3M for any alleged or actual nonconformance to specifications or defect or other failure in products or for 3M's performance of its supply obligations. Under no circumstances is 3M liable for any direct, indirect, incidental, special or consequential damages (including lost profits) in any way related to the product under any theory of law including, but not limited to, negligence and strict liability.

# Ordering Information

Call us at Customer Service to place an order: 800-742-1994 (U.S.). Visit our website: **www.3M.com/medicalspecialties** for product and services information, news about conferences we will be attending, new product highlights or to make a direct inquiry.

To have a sales representative contact you, to request samples or clinical and safety summaries, please contact us at 3M HELPLINE 800-228-3957 (U.S.) or for international inquiries, please contact your local country representative. Our 3M Medical Specialties subsidiary contacts are listed below.