

# Solutions scaled to fit your needs.



Devices shown are not true to size and scale.



## 3M™ Attest™ Dual Auto-reader System 490 and Mini Dual Auto-reader 490M

Get results for both steam and vaporized hydrogen peroxide (VH2O2) in one reader in just 24 minutes.\* 3M offers its dual auto-readers in two sizes to meet your facility's operational needs and budget.



### Increase ease of use

Place any Attest 1491 or 1492V (for steam) or 1295 (for VH2O2) BI in any well of the reader at the same time.



### Raise the standard of care

Help protect patients from the risk of infection with every load monitoring. With fast 24-minute BI results — it's possible.



### Be connected

Connect with 3M product apps to get real time BI results and quickly integrate data into your facility's tracking system.

### Proven innovation you can trust



3M is a leader in rapid self-contained BI technology for steam, vaporized hydrogen peroxide and ethylene oxide.

\*When used with 3M™ Attest™ Auto-reader 490 or 490H with software version 4.2.7 or greater.

# Maximizing space and affordability

With 3M™ Attest™ Dual Auto-reader size options, you can standardize processes and simplify training across multiple facilities.

Our dual auto-readers are compatible with the following 3M™ Attest™ biological indicators:

- 1491 Steam\*
- 1492V Steam\*
- 1295 VH2O2\*



|       | Catalog No. | Product  | Description   | Packaging       | Shipping       |
|-------|-------------|--|---|-----------------|----------------|
| STEAM | 490         | 3M™ Attest™ Dual Auto-reader                         | 22.2(W) x 8.25(H) x 22.2(D) cm  | 1 unit/box      | 1 box/case     |
|       | 490M        | 3M™ Attest™ Mini Dual Auto-reader                    | 15.5(W) x 8.25(H) x 5.25(D) cm  | 1 unit/box      | 1 box/case     |
| STEAM | 41482V      | 3M™ Attest™ Super Rapid 5 Steam-Plus Challenge Pack  | Dynamic-air-removal (Pre-vacuum and SFPP):<br>132°C (270°F) 4 min.<br>135°C (275°F) 3 min.            | 24 each/box     | 1 box/case     |
|       | 41482VF     |  |   | 24 controls/box | 1 box/case     |
|       | 1491        | 3M™ Attest™ Super Rapid Readout Biological Indicator | Gravity:<br>132°C (270°F) 3 min. and 10 min.<br>135°C (275°F) 3 min. and 10 min.                      | 24 each/box     | 5 controls/box |
|       | 1492V       | 3M™ Attest™ Super Rapid Readout Biological Indicator | Dynamic-air-removal (Pre-vacuum and SFPP):<br>132°C (270°F) 3 min. and 4 min.<br>135°C (275°F) 3 min. | 50 each/box     | 4 boxes/case   |
| VH2O2 | 1295        | 3M™ Attest™ Rapid Readout Biological Indicator       | Vaporized Hydrogen Peroxide (VH2O2)   | 30 each/bag     | 4 bags/case    |

Together we can raise the standard of patient care. For more information, contact your 3M representative or visit [go.3M.com/Sterilization](https://go.3M.com/Sterilization).



3M Company  
2510 Conway Ave.  
St. Paul, MN 55144 USA

Phone 1-800-228-3957  
Web 3M.com/Medical

\*Refer to the indications for use provided in the biological indicator Instructions for Use. The indications for use should align with the sterilization cycle to be monitored.

© 2023 3M. All rights reserved. 3M and other marks and/or registered marks of 3M. Unauthorized use prohibited. Please recycle. Printed in USA. EN\_GL\_70-2011-7940-8