

Short-Term Chemical Sanitation of Zeta Plus™ H and MH Series Filter Cartridges With a Chemical Sanitizer (Oxonia Active®)

Introduction

Filters used in Food and Beverage applications are routinely sanitized to reduce the bioburden populations and provide a sanitized (if not sterile) environment during production. Hot water sanitation is generally preferred over chemical treatments for short-term sanitation. It is typically applied prior to the beginning of a production run and at the end of a production run, to sanitize the production equipment. When the use of hot water cannot be conveniently employed, chemical sanitation is the preferred and recommended procedure.

Oxonia Active® (a commercial sanitizer produced by Ecolab, Inc. containing a mixture of hydrogen peroxide and peroxyacetic acid) can be easily employed for chemical sanitation. The temperature, concentration, and duration of the sanitation cycle are important considerations when using this chemical sanitizer. In general, these parameters should be optimized to ensure proper sanitation and if required, should be validated on-site. An equally important consideration is the compatibility of the filter media with the sanitizer of choice, in this case Oxonia Active.

At all times, consideration should be given to worker safety and compliance with local regulations regarding the use of sanitizing chemicals.

Recommended Short Term Sanitation Guidelines

- At the end of the filtration cycle, warm water regenerate the filter according to 3M Technical Brief 70020253400 (Warm Water Regeneration of Zeta Plus™ series and LifeASSURE series filters).
- Drain the filter housing of the remaining warm water. Do not proceed to the chemical sanitation step until the filter housing has cooled to ambient temperature.
- Slowly fill the filter housing with Oxonia Active at a maximum concentration of 1.0% v/v. Follow all safety precautions provided by the sanitizer supplier.
- Once the filter housing is filled with Oxonia Active, close all housing valves and allow the sanitizer to remain in the housing for 30 minutes.
- After sanitizing, and before use, drain the sanitizing solution from the filter housing. Follow all safety precautions and disposal recommendations provided by the sanitizer supplier.
- To remove any residual sanitizing solution in the filter media, flush the filter in the forward direction for 15 minutes with filtered, ambient temperature water at a flux rate of 0.5 gpm/ft² of filter media installed.
- Zeta Plus H series media and MH series media can be exposed to Oxonia Active at a maximum concentration of 1.0% v/v for a maximum of 40, 30 minute cycles.

Additional technical service can be provided by your local 3M Purification Inc. Distributor or the 3M Purification Scientific Applications Support Services (SASS) department, (800) 243-6894.

Important Notice

The information described in this literature is accurate to the best of our knowledge. A variety of factors, however, can affect the performance of the product(s) in a particular application, some of which are uniquely within your knowledge and control. **INFORMATION IS SUPPLIED UPON THE CONDITION THAT THE PERSONS RECEIVING THE SAME WILL MAKE THEIR OWN DETERMINATION AS TO ITS SUITABILITY FOR THEIR USE. IN NO EVENT WILL 3M PURIFICATION INC. BE RESPONSIBLE FOR DAMAGES OF ANY NATURE WHATSOEVER RESULTING FROM THE USE OF OR RELIANCE UPON INFORMATION.**

It is your responsibility to determine if additional testing or information is required and if this product is fit for a particular purpose and suitable in your specific application.

3M PURIFICATION INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

Limitation of Liability

3M Purification Inc. will not be liable for any loss or damage arising from the use of the Product(s), whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. Some states and countries do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation may not apply to you.



3M Purification Inc.

400 Research Parkway
Meriden, CT 06450
U.S.A.
(800) 243-6894
(203) 237-5541
Fax (203) 630-4530
www.3Mpurification.com

Your Local Distributor:

3M is a trademark of 3M Company.
Zeta Plus is a trademark of 3M Company used under license.
© 2013 3M Company. All rights reserved.
Please recycle. Printed in U.S.A.
70020292622 REV 0213b