

3M™ Water Filtration Products

3M™ Aqua-Pure™ Drinking Water Replacement Cartridges

Models EP25 & EP35R

Applications: Drinking water filters for public or private drinking water supply systems.

EP25: Reduces sediment/rust, chlorine taste & odor, lead, mercury, cryptosporidium parvum cyst, asbestos, and select VOC.

EP35R: Reduces sediment/rust, chlorine taste & odor, chloramine, lead, cryptosporidium parvum cyst, VOC*, TTHM, and MTBE.

The 3M™ Aqua-Pure™ Drinking Water Replacement Cartridges are a great choice in water filtration and provide long cartridge life and high sediment reduction efficiency. An advanced dual stage carbon-block filtration process provides cleaner, clearer, better tasting drinking water.

Product Benefits:

- Design compatible with current and previous competitive systems
- Specially formulated blend of high adsorption carbon media for the reduction of unwanted chlorine taste and odor
- Premium depth filtration provides long cartridge life and high sediment reduction efficiency
- Particulate reduction down to 0.5 micron nominal
- Submicron filtration helps reduce water-borne *cryptosporidium* cyst parasites
- Suitable for drinking water, cooking water, and food applications
- Less frequent cartridge change-outs than typical drop-in style cartridges means greater cost savings
- Sanitary Quick Change (SQC) encapsulated cartridges reduce contamination of media during change-outs
- No preactivation required



3M Aqua-Pure Model EP25

Product Specifications:

- Cartridge is certified to NSF Standard 42 and 53
- Cartridge has a maximum operating pressure of 125 psi (862 kPa) and operating temperature of 100°F (37.8°C)



3M Aqua-Pure Model EP35R

Model Number	3M ID	JDE ID	Micron Ratings	Flow Rate (gpm/lpm)	Capacity (gal/lit)	Claims
EP25 (55924-03)	70020319631	5631611	0.5 micron	0.6 gpm	1,150 gals. (4,353 lit.)	Particulate, chlorine taste and odor, parasitic protozoan cysts, asbestos, benzene, lead, mercury, atrazine, lindane, p-Dichlorobenzene, carbofuran and 2, 4-D reduction
				(2.3 lpm)		
EP35R (55924-04)	70020319698	5631616	0.5 micron	0.5 gpm	350 gals. (1,325 lit.)	Particulate, chlorine taste and odor, parasitic protozoan cysts, asbestos, chloramine, lead, MTBE, trihalomethanes (TTHM), and VOC*
				(1.9 lpm)		

*The category of VOC (Volatile Organic Chemical) includes a number of chemicals that are both man-made and naturally occurring. Water from wells and utilities may contain some of these contaminants. Some VOCs are pesticides, herbicides, or insecticides that seep into the ground water after application. Other VOCs enter the water supply through industrial or other waste disposal. This category also includes total trihalomethanes, which are a by-product of chlorination.

3M™ Aqua-Pure™ Drinking Water Replacement Cartridges

Models EP25 & EP35R

Spec # _____

Quantity _____

Model # _____

Part # _____

Important Installation Tips:

These installation tips are for informational purposes only and are not intended to be used as actual installation instructions.

⚠ **WARNING:** Read entire product manual and Performance Data Sheet. Failure to follow all product instructions could cause personal injury from exposure to contaminants AND/OR property damage due to water leakage or flooding.

- System installation and use must comply with all state and local regulations and plumbing codes.
- DO NOT use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.
- If your water supply pressure is higher than 80 psi, you must install a pressure reducing valve before installing system.
- Filter cartridge must be replaced at the required intervals as stated on the product label and manual.
- For cold water use only.
- The 3M Brand EP25 and EP35R Drinking Water Cartridges have been tested and certified to NSF/ANSI standard 42 and 53 for the reduction of the substances listed in the system Performance Data Sheet. The system does not reduce all substances that could be present in your water.

For Performance Data Sheet go to 3M.com/waterquality or contact 3M at 1-866-990-9785.

For additional product information, including product manual and spec sheets, contact 3M at 1-866-990-9785.

For additional information on cartridge replacements please go to 3M.com/waterquality.

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors can affect whether a 3M product is appropriate for a particular application and how it performs, including local water and plumbing conditions. Customer is solely responsible for determining whether a 3M product meets customer's specific application requirements, including testing incoming source water quality and comparing it to the product's capabilities described in the Performance Data Sheet. Failure to properly evaluate, select, use or maintain a 3M product, or to meet applicable regulations or instructions, may result in personal injury from exposure to contaminants AND/OR property damage due to water leakage or flooding.

Limited Warranty, Limited Remedy, and Disclaimer: 3M warrants that this product (excluding filter cartridge or filter membrane) will be free from defects in material and manufacture for the period of one (1) year from the date of purchase. No warranty is given as to the service life of any filter cartridge or membrane as it will vary with local water conditions and water consumption. Except as required by law, 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. This warranty does not cover failures resulting from misuse, alterations, failure to follow instructions or damage not caused by 3M. This warranty does not cover labor. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

This warranty gives you specific legal rights, and you may have other rights which may vary from state to state, or country to country. For warranty questions or service, please call 866.990.9785. Proof of purchase must accompany a warranty claim.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



3M Purification Inc.
3M Separation and Purification Sciences
Division

400 Research Parkway
Meriden, CT 06450 U.S.A.

Toll Free 1-866-990-9785
Worldwide 1-203-237-5541
Web www.3M.com/waterquality



System tested and certified by NSF International against NSF/ANSI 42 and 53 for the reduction of the claims specified on the Performance Data Sheet.

3M and Aqua-Pure are trademarks of 3M Company. NSF is a trademark of NSF International.

© 2022 3M Company. All rights reserved.
70-0201-9246-7 REV 0822
Please recycle. Printed in U.S.A.