


# USG SHEETROCK® BRAND LAY-IN GYPSUM CEILING PANELS

CLIMAPLUS™ PERFORMANCE



USG Sheetrock® Brand  
Lay-In Gypsum Ceiling Panels  
with ClimaPlus™ Performance/  
USG Donn® Brand ZXL™ Acoustical  
Suspension System

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)



Flat White  
050

## FEATURES AND BENEFITS

- USG Clean Room™ panels have a vinyl-laminated face with sealed back and edges for use in cleanroom environments up to Class 100/ISO 5.
- Washable and scrubbable finish, impact and scratch resistant.
- USDA Certified Biobased Product.<sup>7</sup>
- Panels meet USDA/FSIS requirements for food processing areas.
- ClimaPlus™ 30 year limited system warranty against visible sag.

## APPLICATIONS

- Kitchens and Food Preparation Areas
- Restrooms and Utility Areas
- Locker Rooms
- Parking Garages
- Exterior Protected Soffits

## SUBSTRATE

- Gypsum Panel

Smooth-Textured Panel - Vinyl

# USG SHEETROCK® BRAND LAY-IN GYPSUM CEILING PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE  
USG: usg.com or samplitt@usg.com  
CGC: contact Sales Representative

FOR MOST UP-TO-DATE  
TECHNICAL INFORMATION  
AND LEED REPORT TOOL  
usgdesignstudio.com  
cgcdesignstudio.com  
usg.ecomedes.com

TECHNICAL SERVICES  
800.USG.4YOU (874-4968)



PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS:  
ULCOM/GG  
UL 2818



USG SHEETROCK® BRAND  
LAY-IN GYPSUM  
CEILING PANEL

USG SHEETROCK® BRAND  
LAY-IN GYPSUM CEILING  
PANEL CLEAN ROOM™ 5

Edge	Panel Size	Fire Class <sup>2</sup>	Item No.	NRC <sup>4</sup>	CAC Min.	LR <sup>3</sup>	Color	Abuse Resistant	Grid Options	VOC Emissions	Recycled Content <sup>1</sup>	Panel Cost
SQ 	2'x2'x1/2"		3260	-	35	0.77	White		A, B, C, D	Low	8%	\$
	2'x4'x1/2"		3270	-	40	0.77	White		A, B, C, D	Low	8%	\$
SQ 	2'x4'x1/2"		3200	-	40	0.77	White		A, B, C, D	Low	8%	\$\$

**Low Emissions (VOC)**

Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.



GRID PROFILE OPTIONS

A USG DXL™	B USG DXLA™	C USG ZXLA™	D <sup>6</sup> USG DXWCE™

PHYSICAL DATA

**ASTM E1264 classification**  
ASTM E1264-22 Type XX, Pattern G  
ASTM E1264-23 Type G, Form G2, Pattern G

**ASTM E84 and CAN/ULC S102 surface-burning characteristics**  
Class A  
Flame spread: 25 or less  
Smoke developed: 50 or less

**UL Type**  
FC-CB

**Weight**  
2.00 lb./sq. ft.

**Online tools**  
usgdesignstudio.com, cgcdesignstudio.com  
or usg.ecomedes.com

**Thermal resistance**  
R-0.45

**Maximum backloading**  
See *USG 30-Year Limited System Warranty Commercial Applications (SC2102)*.

**Maintenance**  
Can be cleaned easily with a damp sponge. Use mild detergent and water—do not use acetate, ammonia or high concentration of chlorine, bromide or other harsh chemicals.

**Application considerations**  
Product is directional. Install with all manufactured edges parallel and in the same direction.

**Notes**

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
- Firecode® products are approved for use in fire-resistance rated UL designs, where the designs allow for the UL Type Designation.
- LR values are shown as averages.
- USG does not consider a ceiling panel to be acoustically rated if NRC is less than 0.50.
- Field-cut edges of USG Clean Room™ panels must be sealed with white latex paint.
- Cleanroom-rated applications require a suspension system with gasketed tee flanges such as USG Donn® Brand AXCE™, DXCE™, DXWCE™ or DXACE™.
- This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on biopreferred.gov website.

**Notice**  
The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC1820/rev. 7-25  
© 2025 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by  
United States Gypsum Company  
550 West Adams Street  
Chicago, IL 60661

The trademarks USG, CGC, AXCE, CLEAN ROOM, CLIMAPLUS, DONN, DXACE, DXCE, DXL, DXLA, DXWCE, FIRECODE, SHEETROCK, ZXLA, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

