

# USG TOUCHSTONE™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Touchstone™ Acoustical Panels with ClimaPlus™ Performance, and USG Donn® Brand DX® Acoustical Suspension System

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)



Flat White  
050

## FEATURES AND BENEFITS

- Panels are scuff and abuse resistant and can withstand day-to-day activity in high traffic areas.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- Firecode® product designed to meet life-safety codes.

## APPLICATIONS

- Schools
- General Offices
- Retail Stores

## SUBSTRATE

- Wet-formed Mineral Fiber

Medium-Textured Panel

# USG TOUCHSTONE™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE  
USG: usg.com or samplitt@usg.com  
CGC: contact Sales Representative

FOR MOST UP-TO-DATE  
TECHNICAL INFORMATION  
AND LEED REPORT TOOL  
usgdesignstudio.com  
cgcdesignstudio.com  
usg.ecomedes.com

TECHNICAL SERVICES  
800.USG.4YOU (874-4968)



PRODUCT CERTIFIED  
FOR LOW CHEMICAL  
EMISSIONS:  
ULCOM/GG  
UL2818

30 YEAR LIMITED SYSTEM  
WARRANTY  
• No Visible Sag  
• Mold/Mildew Protection

UL Classified

| Edge    | Panel Size | Fire Class <sup>2</sup> | Item No. | NRC  | CAC Min. | LR <sup>3</sup> | Color | Grid Options | VOC Emissions | Anti-Mold & Mildew/Sag Resistance | Abuse Resistant | Recycled Content <sup>1</sup> | Panel Cost |
|---------|------------|-------------------------|----------|------|----------|-----------------|-------|--------------|---------------|-----------------------------------|-----------------|-------------------------------|------------|
|         |            |                         |          |      |          |                 |       |              |               |                                   |                 |                               |            |
| SQ<br>  | 2'x2'x5/8" |                         | 5893     | 0.55 | 35       | 0.86            | White | A,B          | Low           |                                   |                 | 65%                           | \$\$       |
|         | 2'x4'x5/8" |                         | 5894     | 0.55 | 35       | 0.86            | White | A            | Low           |                                   |                 | 65%                           | \$\$       |
| SLT<br> | 2'x2'x5/8" |                         | 5896     | 0.55 | 35       | 0.86            | White | C            | Low           |                                   |                 | 65%                           | \$\$       |

### Low Emissions (VOC)

Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

### ClimaPlus™ Warranty Performance<sup>4</sup>

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

### Firecode®

Abuse Resistant

### GRID PROFILE OPTIONS

| A<br>USG DXL™ | B <sup>5</sup><br>USG Centricitee™<br>DXLT™ | C<br>USG DXL™ |
|---------------|---|---------------|
|               |   |               |

### PHYSICAL DATA

#### ASTM E1264 classification

ASTM E1264-22 Type III, Form 2, Pattern C, E, & I  
ASTM E1264-23 Type A, Form A1.2, Pattern C, E, & I

#### ASTM E84 and CAN/ULC S102 surface-burning characteristics

Class A  
Flame spread: 25 or less  
Smoke developed: 50 or less

#### UL Type

FR-83

#### Weight

1.09 lb./sq. ft.

#### Online tools

usgdesignstudio.com, cgcdesignstudio.com or usg.ecomedes.com

#### Thermal resistance

R-1.6

#### Maximum backloading

See USG 30-Year Limited System Warranty Commercial Applications (SC2102).

#### Maintenance

Can be cleaned easily with a soft brush or vacuum.

#### Metric sizes available

Contact sales for minimum quantities and lead times.

#### Notes

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
- Firecode® products are approved for use in fire-resistance rated UL designs, where the designs allow for the UL Type Designation.
- LR values are shown as averages.
- For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
- Maximum 2'x2' with SQ edge panels.

#### Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

#### SC2214/rev. 7-25

© 2025 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by  
USG Interiors, LLC  
550 West Adams Street  
Chicago, IL 60661

The trademarks USG, CGC, CLIMAPLUS, DONN, DXL, DXLT, FIRECODE, TOUCHSTONE, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

