




USG ENSEMBLE™ AIRLESS FINISH

FINE FINISH FOR USG ENSEMBLE®
ACOUSTICAL DRYWALL CEILING

Features and benefits

- Acoustically transparent, technologically advanced formulation
- White color with a fine finish
- High light reflectance (LR-.87)
- Quick drying, recoat in 10-30 minutes*
- Applied with airless spray equipment for economical installation
- Custom Colors - Coming Soon!



USE

Designed specifically as a fine finish for USG Ensemble® Acoustical Drywall Ceiling and Wall System.

BASIC INSTALLATION DATA

For complete installation instructions, see *USG Ensemble® Acoustical Drywall Ceiling Guide (SC5075)*.

MIXING

The USG Ensemble™ Airless Finish must be thoroughly mixed prior to application. Before cycling into the pump, mix the Finish with a high-speed drill fitted with a spiral mixing blade. Mix thoroughly for 2 minutes, or until any settled aggregate is fully suspended and the finish has a smooth consistency. Do not add any water during the mixing process.

RECOMMENDED SPRAY EQUIPMENT

An airless sprayer and a spray gun will be needed to apply the USG Ensemble™ Airless Finish over the USG Sheetrock® Brand Ensemble® Four-Sided Taper™ Panels. Equipment specifications are available from your local USG Sales Representative.

APPLICATION

In order to achieve proper sound performance and appearance, the USG Ensemble™ Airless Finish must be applied in a cross-hatch, half-lap spray pattern. Apply each coat very lightly with 36" min. gun clearance. Start in one corner and work progressively across the ceiling, immediately cross-hatch. After the first coat is applied wait until it is 100% dry (see drying time). Use a soft rubber squeegee trowel to remove any loose Finish from the ceiling. Repeat this step between each coat once dry. Apply successive coats until the desired appearance is achieved. The Finish can be applied directly to primed metal, plastic beads and trims. Maintain proper job site conditions and wear proper personal protective equipment (safety goggles, dust masks, coveralls) while applying texture.

LIMITATIONS

1. For use only with USG Ensemble® Acoustical Drywall Ceiling and Wall Systems.
2. Not for use in areas subject to frequent surface contact
3. Cannot be painted without negatively affecting acoustical performance

PRODUCT DATA

Color: White LR 0.87

Binder: Water-Based Acrylic

Coverage: Approximately 200 ft² per pail (x4 cross hatch half lap coats) on ceilings larger than 500 ft², a 10% overage for waste is recommended. For projects with multiple ceilings that are less than 500 ft² each, a 20% overage for waste is recommended.

Packaging: 5 gal pails filled with 4 gal Finish

Drying Time*: Can be recoated after 10-30 minutes at 75°F/50% R.H. conditions. Drying time is dependent on temperature and humidity of the space.

Storage: Store at 55-95°F (13-35°C) in a dry location. Protect from freezing, extreme heat and exposure to direct sunlight. Keep container tightly sealed. Do not use if material is discolored or has an unpleasant odor. Unopened and unmixed Finish has up to 12-month shelf life under good storage conditions. Opened and mixed Finish has up to 6-month shelf life under good storage conditions. Rotate stock on a first-in, first-out basis.

*In less than ideal drying conditions, you may have to wait 30-60 min between coats. Check surface is dry to the touch before spraying subsequent coats. Using fans for air movement will typically help reduce drying time.

SUBMITTAL APPROVALS

Job Name	
Contractor	Date

PRODUCT INFORMATION
See usg.com for the most up-to-date product information.

CAUTION
May cause irritation to eyes, skin, nose, throat and upper respiratory tract. Use only in a well-ventilated area, wear a NIOSH/MSHA-approved respirator. Wear eye protection. If eye contact occurs, flush thoroughly with water for 15 minutes. If on skin: Wash with plenty of water. If swallowed and/or irritation persists, call a physician. For more information call Product Safety: 800 507-8899 or see the SDS at usg.com **KEEP OUT OF REACH OF CHILDREN.**

TRADEMARKS
The trademarks USG, ENSEMBLE, FOUR-SIDED TAPER, SHEETROCK, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

NOTE
Products described here may not be available in all geographic markets. Consult your USG Company sales office or representative for information.

NOTICE
We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered. Please visit usg.com or cgcinc.com for the full warranty, limits of liability, and other terms and conditions applicable to your product.

SAFETY FIRST!
Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

800 USG.4YOU
800 (874-4968)
usg.com/ensemble

Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

SC433982/5-26
© 2026 USG Corporation and/or
its affiliates. All rights reserved.
Printed in USA

