

USG MARS™ HIGH-NRC/HIGH-CAC ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷



USG Mars™ High-NRC Acoustical Panels with ClimaPlus™ Performance, and USG Donn® Brand Centricitee™ DXT™ Acoustical Suspension System
Lowell Justice Center in Lowell, MA,
Architect: Finegold Alexander Architects, Photo: ©Anton Grassi

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM

FEATURES AND BENEFITS

- Balanced acoustics with a wide range of options: NRC up to 0.95 and CAC up to 40.
- High light-reflective finish (LR-0.90 White products).
- Washable, scrubbable, impact and scratch resistant⁵.
- Coordinates visually with USG Halcyon™ Acoustical Panels for open- or closed-plan applications.
- Nondirectional, monolithic visual reduces installation time and waste.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- GREENGUARD Gold certified for low emitting performance.
- USG Mars™ High-NRC/High-CAC Acoustical Panels are part of the Ecoblueprint™ portfolio — meeting today's sustainability standards. For sustainability documentation go to USG.com or CGCInc.com.


APPLICATIONS

- Offices
- Healthcare
- Classrooms and Corridors
- Reception Areas and Lobbies
- Department Stores and Retail
- Restaurants and Hospitality

SUBSTRATE

- Wet-formed Mineral Fiber

PREMIUM COLORS



STANDARD COLOR



CUSTOM COLOR



Unlimited
Color Options

Fine-Textured Panel

USG MARS™ HIGH-NRC/HIGH-CAC ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷


ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
UL.COM/GG
UL 2818



**USG MARS™
HIGH-NRC PANELS
95/30**
Plant-Based Binder

**USG MARS™
HIGH-NRC PANELS
90/30**
Plant-Based Binder

Edge	Panel Size	Fire Class	Item No.	NRC ⁸	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SQ 	2'x2'x1.3"	Class A	88280	0.95	30	0.90	White	A,B,C	Low		21%	\$\$\$
	2'x4'x1.3"	Class A	88281	0.95	30	0.90	White	A,B	Low		21%	\$\$\$
SL 	2'x2'x1.3"	Class A	88285	0.95	30	0.90	White	I	Low		21%	\$\$\$
	2'x4'x1.3"	Class A	88286	0.95	30	0.90	White	I	Low		21%	\$\$\$
FL 	2'x2'x1.3"	Class A	88290	0.95	30	0.90	White	J,K,L,M	Low		21%	\$\$\$
	2'x4'x1.3"	Class A	88291	0.95	30	0.90	White	J,K,L,M	Low		21%	\$\$\$
SQ 	2'x2'x1"	Class A	88137	0.90	30	0.90	White, color ⁶	A,B,C	Low		71%	\$\$\$
	2'x4'x1"	Class A	89137	0.90	30	0.90	White	A,B	Low		71%	\$\$\$
	30"x30"x1"	Class A	80213	0.90	30	0.90	White	A,B	Low		71%	\$\$\$
	30"x60"x1"	Class A	89143	0.90	30	0.90	White	A,B	Low		71%	\$\$\$
	2'x5'x1"	Class A	89673	0.90	30	0.90	White	A,B	Low		71%	\$\$\$
	2'x6'x1"	Class A	89674	0.90	30	0.90	White	A,B	Low		71%	\$\$\$
SLT 	2'x2'x1"	Class A	88138	0.90	30	0.90	White, color ⁶	D	Low		71%	\$\$\$
	2'x4'x1"	Class A	89138	0.90	30	0.90	White	D	Low		71%	\$\$\$
	30"x30"x1"	Class A	80239	0.90	30	0.90	White	D	Low		71%	\$\$\$
	30"x60"x1"	Class A	89144	0.90	30	0.90	White	D	Low		71%	\$\$\$
	2'x5'x1"	Class A	89675	0.90	30	0.90	White	D	Low		71%	\$\$\$
	2'x6'x1"	Class A	89676	0.90	30	0.90	White	D	Low		71%	\$\$\$
FLB 	2'x2'x1"	Class A	88139	0.90	30	0.90	White, color ⁶	E,F,G,H	Low		71%	\$\$\$
	2'x4'x1"	Class A	89139	0.90	30	0.90	White	E,F,G,H	Low		71%	\$\$\$
	30"x30"x1"	Class A	80265	0.90	30	0.90	White	E,F,G,H	Low		71%	\$\$\$
	30"x60"x1"	Class A	89145	0.90	30	0.90	White	E,F,G,H	Low		71%	\$\$\$
	2'x5'x1"	Class A	89677	0.90	30	0.90	White	E,F,G,H	Low		71%	\$\$\$
	2'x6'x1"	Class A	89678	0.90	30	0.90	White	E,F,G,H	Low		71%	\$\$\$

Low Emissions (VOC)

Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Methodology of calculation based on FTC guidelines.

USG MARS™ HIGH-NRC/HIGH-CAC

ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷

ORDER SAMPLES/LITERATURE
USG: usg.com or samplit@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800.USG.4YOU (874-4968)

ECOBLUEPRINT

Declare



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
UL.COM/GG
UL 2818

30 YEAR LIMITED SYSTEM
WARRANTY
• No Visible Sag
• Mold/Mildew Protection

BALANCED
ACOUSTICS

HRC HIGH
RECYCLED
CONTENT

P PREMIUM
COLOR
PALETTE

CUSTOM
COLOR



USG MARS™ HIGH-NRC PANELS 85/35

Plant-Based Binder

USG MARS™ HIGH-NRC/ HIGH-CAC PANELS 80/40

Plant-Based Binder

USG MARS™ HIGH-NRC PANELS 80/35

Plant-Based Binder

UL Classified ⁵												
Edge	Panel Size	Fire Class	Item No.	NRC ⁸	CAC Min.	LR ⁷	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SQ	2'x2'x7/8"	Class A	88134	0.85	35	0.90	White, color ⁶	A,B,C	Low		72%	\$\$\$
	2'x4'x7/8"	Class A	89134	0.85	35	0.90	White	A,B	Low		72%	\$\$\$
	30"x30"x7/8"	Class A	80113	0.85	35	0.90	White	A,B	Low		72%	\$\$\$
	30"x60"x7/8"	Class A	89140	0.85	35	0.90	White	A,B	Low		72%	\$\$\$
	2'x5'x7/8"	Class A	89662	0.85	35	0.90	White	A,B	Low		72%	\$\$\$
	2'x6'x7/8"	Class A	89663	0.85	35	0.90	White	A,B	Low		72%	\$\$\$
SLT	2'x2'x7/8"	Class A	88135	0.85	35	0.90	White, color ⁶	D	Low		74%	\$\$\$
	2'x4'x7/8"	Class A	89135	0.85	35	0.90	White	D	Low		74%	\$\$\$
	30"x30"x7/8"	Class A	80139	0.85	35	0.90	White	D	Low		74%	\$\$\$
	30"x60"x7/8"	Class A	89141	0.85	35	0.90	White	D	Low		74%	\$\$\$
	2'x5'x7/8"	Class A	89664	0.85	35	0.90	White	D	Low		72%	\$\$\$
	2'x6'x7/8"	Class A	89665	0.85	35	0.90	White	D	Low		72%	\$\$\$
FLB	2'x2'x7/8"	Class A	88136	0.85	35	0.90	White, color ⁶	E,F,G,H	Low		74%	\$\$\$
	2'x4'x7/8"	Class A	89136	0.85	35	0.90	White	E,F,G,H	Low		74%	\$\$\$
	30"x30"x7/8"	Class A	80165	0.85	35	0.90	White	E,F,G,H	Low		74%	\$\$\$
	30"x60"x7/8"	Class A	89142	0.85	35	0.90	White	E,F,G,H	Low		74%	\$\$\$
	2'x5'x7/8"	Class A	89667	0.85	35	0.90	White	E,F,G,H	Low		72%	\$\$\$
	2'x6'x7/8"	Class A	89668	0.85	35	0.90	White	E,F,G,H	Low		72%	\$\$\$
SQ	2'x2'x1"	Class A	86345	0.80	40	0.90	White	A,B,C	Low		74%	\$\$
	2'x4'x1"	Class A	88345	0.80	40	0.90	White	A,B	Low		74%	\$\$
SLT	2'x2'x1"	Class A	86346	0.80	40	0.90	White	D	Low		74%	\$\$
	2'x4'x1"	Class A	88346	0.80	40	0.90	White	D	Low		74%	\$\$
FLB	2'x2'x1"	Class A	86347	0.80	40	0.90	White	E,F,G,H	Low		74%	\$\$
	2'x4'x1"	Class A	88347	0.80	40	0.90	White	E,F,G,H	Low		74%	\$\$
SQ	2'x2'x7/8"	Class A	86100	0.80	35	0.90	White	A,B,C	Low		74%	\$\$
	2'x4'x7/8"	Class A	86300	0.80	35	0.90	White	A,B	Low		74%	\$\$
	30"x30"x7/8"	Class A	86426	0.80	35	0.90	White	A,B	Low		74%	\$\$
	30"x60"x7/8"	Class A	86429	0.80	35	0.90	White	A,B	Low		74%	\$\$
	2'x5'x7/8"	Class A	86350	0.80	35	0.90	White	A,B	Low		74%	\$\$
	2'x6'x7/8"	Class A	86360	0.80	35	0.90	White	A,B	Low		74%	\$\$

Low Emissions (VOC)

Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

HRC High Recycled Content

USG classifies High Recycled Content as greater than 50%. Methodology of calculation based on FTC guidelines.

USG MARS™ HIGH-NRC/HIGH-CAC ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE WITH PLANT-BASED BINDER⁷

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS
ULCOM/GG
UL 2818

30 YEAR LIMITED SYSTEM
WARRANTY
• No Visible Sag
• Mold/Mildew Protection

BALANCED
ACOUSTICS

HRC HIGH
RECYCLED
CONTENT

P PREMIUM
COLOR
PALETTE

CUSTOM
COLOR



ECOBUEPRINT

Declare.

USG MARS™
HIGH-NRC PANELS
80/35
Plant-Based Binder

USG MARS™
HIGH-CAC PANELS
60/40

Edge	Panel Size	Fire Class	Item No.	NRC ⁸	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SLT 	2'x2'x7/8"	Class A	87200	0.80	35	0.90	White	D	Low		74%	\$\$
	2'x4'x7/8"	Class A	89600	0.80	35	0.90	White	D	Low		74%	\$\$
	30"x30"x7/8"	Class A	86500	0.80	35	0.90	White	D	Low		74%	\$\$
	30"x60"x7/8"	Class A	86466	0.80	35	0.90	White	D	Low		74%	\$\$
	2'x5'x7/8"	Class A	89650	0.80	35	0.90	White	D	Low		74%	\$\$
	2'x6'x7/8"	Class A	89660	0.80	35	0.90	White	D	Low		74%	\$\$
FLB 	2'x2'x7/8"	Class A	87100	0.80	35	0.90	White	E,F,G,H	Low		74%	\$\$
	2'x4'x7/8"	Class A	89500	0.80	35	0.90	White	E,F,G,H	Low		74%	\$\$
	30"x30"x7/8"	Class A	86400	0.80	35	0.90	White	E,F,G,H	Low		74%	\$\$
	30"x60"x7/8"	Class A	86497	0.80	35	0.90	White	E,F,G,H	Low		74%	\$\$
	2'x5'x7/8"	Class A	89550	0.80	35	0.90	White	E,F,G,H	Low		74%	\$\$
	2'x6'x7/8"	Class A	89670	0.80	35	0.90	White	E,F,G,H	Low		74%	\$\$
SQ 	2'x2'x3/4"	Class A	86186	0.60	40	0.90	White, color ⁶	A,B,C	Low		76%	\$\$\$
	2'x4'x3/4"	Class A	87187	0.60	40	0.90	White	A,B	Low		76%	\$\$\$
SLT 	2'x2'x3/4"	Class A	86786	0.60	40	0.90	White, color ⁶	D	Low		76%	\$\$\$
	2'x4'x3/4"	Class A	88786	0.60	40	0.90	White	D	Low		76%	\$\$\$
FLB 	2'x2'x3/4"	Class A	86986	0.60	40	0.90	White, color ⁶	E,F,G,H	Low		76%	\$\$\$
	2'x4'x3/4"	Class A	88986	0.60	40	0.90	White	E,F,G,H	Low		76%	\$\$\$

Low Emissions (VOC)

Certified for low emitting performance, meets CDPH 01350 v1.2 - 2017. Certificates of Compliance for Low VOC Emissions are available on usg.com and at usg.ecomedes.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Methodology of calculation based on FTC guidelines.

GRID PROFILE OPTIONS

A USG DX*	B USG DXW™	C ⁴ USG Centricitee™ DXT™	D USG DX*	E USG Centricitee™ DXT™	F USG Finline® DXF™	G USG Finline® 1/8 DXFF™	H USG Identitee® DXI™
I USG DX*	J USG Centricitee™ DXT™	K USG Finline® DXF™	L USG Finline® 1/8 DXFF™	M USG Identitee® DXI™			

PHYSICAL DATA

ASTM E1264 classification

ASTM E1264-22: Type IV, Form 1 and 2, Pattern E, G
ASTM E1264-23: Type A, Form A2.1 and A2.2, Pattern E, G

ASTM E84 and CAN/ULC S102 surface-burning characteristics

Class A
Flame spread: 25 or less
Smoke developed: 50 or less

Weight
1.09 - 1.36 lb./sq.ft.

Online tools
usgdesignstudio.com, cgcdesignstudio.com
or usg.ecomedes.com

Thermal resistance

R-2.2 (3/4" panels)
R-4.5 (1.3" panels)

Maximum backloading

See USG 30-Year Limited System Warranty Commercial Applications (SC2102).

Maintenance

Can be cleaned easily with a soft brush or vacuum. To clean white panels, use a clean, white cloth with water or a mild detergent and wipe surface.

Metric sizes available

Contact sales for minimum quantities and lead times.

Notes

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
- LR values are shown as averages.
- For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
- Maximum 2'x2' with SQ edge panels.
- Acoustic values, washability, scrubability, impact, and scratch resistance are for white panels. Color may impact performance based on color selected.
- See Colors selector for more information.
- All USG Mars™ High-NRC Acoustical Panels with a "plant-based binder" label contain up to 65% plant-based material in the binder. For more information, please refer to the USG Mars Acoustical Panels Health Product Declaration, available at www.usg.com.
- It is not recommended to mix panels with varying NRC values in the same ceiling plane.

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2487/rev. 8-26

© 2026 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXT, DXW, ECOBLUEPRINT, FINELINE, HALCYON, IDENTITEE, MARS, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

